

27 Inches 100Hz Display

MW-LC27-E



Features


- Resolution is up to at 1920 x 1080.
- Refresh rate up to 100 Hz.
- 178° horizontal and vertical viewing angle.
- Screen can reduce blue light, protect eyes.
- Plastic body, ultra-narrow bezel, light weight and elegant.
- Shielding cover design, effectively preventing electromagnetic radiation.
- Stable structure design, highly durable.
- Automatically detect if the signal is connected successful.
- Support multiple language.

Specifications


Panel	Description
Backlight	LED
Panel Size	27"
Pixel Pitch (H x V) (mm)	0.31 x 0.31
Resolution	1920 x 1080
Display Size (mm)	597.9 x 336.8
Color Support	16.7 M
Brightness (cd/m ²)	250

Contrast Ratio	4000:1
Refresh Rate	100 Hz
Response Time (ms)	5
Viewing Angle (H/V)	Horizontal 178° , Vertical 178°
Operation Hour	18/7
Interface	Description
Video Input	1 x HDMI(1920 x 1080@100 HZ), 1 x VGA(1920 x 1080@60 HZ)
VESA	Description
VESA (mm)	75 x 75
Wall-mounted Thread	4-M4 Threaded Hole, 8mm Deep Thread
OSD	Description
Multi-Language	Chinese, English, German, French, Italian, Spanish, Portuguese, Turkish, Polish, Dutch, Japanese, Korean
General	Description
Input Voltage	DC 12 V, 3 A
Typical Power Consumption (W)	≤36
Standby Power Consumption (W)	≤0.5
Product Dimensions (W x H x D) (mm)	614.1 x 363.0 x 51.1
Package Dimensions (W x H x D) (mm)	694 x 458 x 114
Weight (Kg)	Net Weight: 3.84 Gross Weight: 5.25
Operating Temperature	0°C ~ 40°C
Operating Humidity	10% ~ 85% (No Condensation)
Storage Temperature	-20°C ~ 60°C
Storage Humidity	5% ~ 90% (No Condensation)
Standard	1 x HDMI Cable, 1 x Quick Guide, 1 x Pedestal, 1 x Adapter

Dimensions



Interface



Ordering Info

Product Model	Description
MW-LC27-E	27 Inches 100Hz Display

Zhejiang Uniview Technologies Co., Ltd.

No. 369, Xietong Road, Xixing Sub-district, Binjiang District, Hangzhou City, 310051, Zhejiang Province, China

Email: overseasbusiness@uniview.com; globalsupport@uniview.com

<http://www.uniview.com>

©2024 Zhejiang Uniview Technologies Co., Ltd. All rights reserved.

*Product specifications and availability are subject to change without notice.

*Despite our best efforts, technical or typographical errors may exist in this document. Uniview cannot be held responsible for any such errors and reserves the right to change the contents of this document without prior notice.