# Eaton 9E10KI

# Catalog Number: 9E10KI

Eaton 9E UPS, 10 kVA, 8 kW, Input: Hardwired, Output: Hardwired, Tower

# General specifications



Eaton 9E UPS

UPC

743172067678

Product Height

70.85 cm

**Product Weight** 

85.39 kg

Certifications

IEC/EN 62040-1 IEC/EN 62040-2

CE

EAC

Catalog Number

9E10KI

Product Length/Depth

61.29 cm

**Product Width** 

26.24 cm

Compliances

CE Marked

TUV



# Battery

Battery type

Sealed, lead-acid

Runtime graph

\$row.attributeValue.cdata

Battery replacement

Replacable batteries

Battery quantity

20

Battery management

Automatic battery test

Deep discharge protection

Battery rating

12 V / 9 Ah

Extended battery capability

Yes

#### Electrical output

Voltage

230V

Wattage

8 kW

Output power factor

0.8

Output voltage range

220/230/240 V +/- 2%

Output waveform

Sine wave

Output nominal voltage

230V default (220/230/240V)

Voltage distortion output (linear load) - max

3

Feed type

1

**Topology** 

Online/Double-conversion

VA rating

10 kVA

# Electrical input

# Input connection

Hardwired/fixed connection

Input nominal voltage

400V/230V

Nominal frequency

50/60 Hz

Input power factor

>.99

Input voltage range

176-276 V (110-276 V with derating) for 1ph input

Input frequency range

45-66Hz

#### Communications

#### Includes network card

No

### Communication

USB port (HID compliant)

Serial port (RS232)

Mini-terminal block for

remote power off

Communication slot

#### Ethernet interface

No

User interface

LCD Display

Potential free switch contact

Yes

**Expansion slots** 

One slot for optional communication card

Software compatibility

Eaton Intelligent Power Manager, Eaton Intelligent Power

Protector

Type of interface

Other

#### **Environmental**

Altitude

3000 m

Noise level

<55 dB at 1 meter

Temperature range

0° to 40°C (32° to 104°F)

Relative humidity

0-95% non-condensing

# Additional specifications

Construction type

Free standing model

Package contents

**UPS** 

USB cable

Serial cable

User manual

Phase (output)

1

Internal bypass

Yes

Auto shutdown function

Yes

Color

Black

Efficiency

92

Rack mounting kit

No

Phase (input)

1 or 3

Hot swap power

No

#### Resources

Compliance information

EU declaration of conformity Eaton 9E UPS

Declarations of conformity

EU Declaration of Conformity

Manuals and user guides

Eaton 9E UPS - User Manual

Eaton 9E UPS - Installation and user manual

Technical data sheets

Eaton 9E UPS - Datasheet



Eaton Corporation plc Eaton House 30 Pembroke Road Dublin 4, Ireland Eaton.com

© 2024 Eaton. All rights reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.

