





# APC Back-UPS, 2200VA, Tower, 230V, 4x CEE 7/5 French Schuko outlets, AVR

BX2200MI-FR

#### Overview

Lead time Usually in Stock

#### Main

IVIAIII	
Main Input Voltage	230 V
Rated power in W	1200 W
Rated power in VA	2200 VA
Product or component type	Uninterruptible power supply (UPS)
Input Connection Type	French/Belgian
output connection type	4 French
Cable length	1.2 m
Number of cables	1
Battery type	Lead-acid battery

#### **Batteries & Runtime**

Run Time	View Runtime Graph ☐
Efficiency	View Efficiency Graph ☐
Battery recharge time	8 h
Battery voltage	24 V
Battery capacity	9.0 Ah
Battery life	35 year(s)
Replacement battery	APCRBC177 ☐
Battery graph comments	Curve fit to measured runtime data. All measurements taken with new, fully charged batteries, at typical environmental conditions, with no electrical input and balanced resistive load (PF = 1.0) output.
Extended runtime	0

#### **General**

Provided equipment	user manual
Number of power module filled slots	0
Redundant	No

#### **Physical**

Colour Black

Excluding VAT, FCA Jabal Ali & are subject to change – check with your local distributor.

Height	19 cm
Width	14 cm
Depth	39 cm
Net weight	12.3 kg
Mounting preference	No preference
mounting mode	Not rack-mountable

# Input

Network frequency	50/60 Hz +/- 5 Hz auto-sensing
Plug standard	French/Belgian
Input voltage limits	140300 V
Input Power Factor at Full Load	0.54

# Output

Maximum configurable power in W	1200 W
Output frequency	50/60 Hz +/- 1 Hz sync to mains
UPS type	Line interactive
Wave type	Stepped approximation to a sinewave
Full load runtime	00:01:00 1200 W
Half load runtime	00:08:30 600 W
Maximum configurable power in VA	2200 VA
Transfer time	6 ms typical : 10 ms maximum

#### Conformance

product certifications	CE CB
Standards	EN/IEC 62040-1:2019/A11:2021 EN/IEC 62040-2:2006/AC:2006 EN/IEC 62040-2:2018
Equipment protection policy	Lifetime : 50000 euros

#### **Environmental**

Ambient air temperature for operation	040 °C
Relative humidity	095 % non-condensing
Operating altitude	03000 m
Ambient air temperature for storage	-1540 °C
Storage Relative Humidity	095 % non-condensing
Storage altitude	03000 m
acoustic level	40 dBA
IP degree of protection	IP20

# **Communications & Management**

Control panel LED Status display with on line : on battery

# **Surge Protection and Filtering**

Surge energy rate 273 J

# **Packing Units**

_	
Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	29.7 cm
Package 1 Width	23.5 cm
Package 1 Length	49.5 cm
Package 1 Weight	13.6 kg
SCC14	10731304420511

# **Contractual warranty**

Warranty 2 years repair or replace



**Green Premium**<sup>TM</sup> **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

#### Well-being performance

✓ Toxic Heavy Metal Free
 ✓ Mercury Free
 ✓ Rohs Exemption Information

#### **Certifications & Standards**

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant EU RoHS Declaration
China Rohs Regulation	China RoHS declaration  Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information

### **Product datasheet**

BX2200MI-FR

Image of product / Alternate images

**Alternative** 





# BX2200MI-FR

