

APC Smart-UPS On-Line, 10kVA/ 10kW, Tower, 230V/400V, 6x C13+4x C19 IEC outlets, Network Card+SmartSlot, Extended runtime, W/O rail kit

SRT10KXLI

Overview

Presentation	High density, double-conversion on-line power protection with scalable runtime.
Lead time	Usually in Stock
Main	
Main Input Voltage	230 V

Uninterruptible power supply (UPS)

240 V
380 V
415 V

Product or Component Type

Other Input Voltage

Main Output Voltage

Kw Rating

Other Output Voltage	220 V
	240 V

Rated power in VA	10000 VA	
output connection type	6 IEC 60320 C1	

	4 120 00020 019
	4 IEC 60320 C19
	3 IEC Jumpers

Output connector type	Hard Wire 3-wire (H N + E) 1
Provided equipment	CD with software

Documentation (CD
Installation guide	9
Temperature Pro	be
USB cable	
Warranty card	

Web/SNMP Management Card

400 V 3 phase

220 V

230 V

10000 W

Range of Product Smart-UPS On-Line

Batteries & Runtime

Run Time	View Runtime Graph ☐
Efficiency	View Efficiency Graph ☐
Battery Type	Lead-Acid battery
Included Battery Modules	0
Typical recharge time	1.5 h
RBC Quantity	2
Battery Voltage	+/-192 V (split battery referenced to neutral)

Battery Charge Power (Watts)	876 W rated
Battery Life	35 year(s)
Replacement battery	APCRBC140 ☐
	SRT192BP2US ☐
	SRT192RMBPUS ☐
Extendable Run Time	

General

Topology	Double Conversion Online
product web sub-family	High density
Number of power module free slots	0
Number of power module filled slots	0
Redundant	No

Physical

_	
color	Black
Height	17.008 in (43.2 cm)
Width	10.4 in (26.3 cm)
Depth	28.1 in (71.5 cm)
Net Weight	246.52 lb(US) (111.82 kg)
mounting location	Front
Mounting preference	No preference
Mounting Mode	Rack-mounted with kit
Two post mountable	0
USB compatible	Yes

Input

Input Frequency	40 - 70 Hz auto-sensing
Number of input connectors	1 Hard Wire 3-wire (1PH+N+G) 1 Hard Wire 5-wire (3PH + N + G)
Efficiency at full load	100275 V adjustable (half load) 173476 V adjustable (half load)

Output

Maximum configurable power in VA	10000 VA
Max Configurable Power (Watts)	10000 W
Output Frequency (sync to mains)	50/60 Hz +/- 3 Hz sync to mains
Waveform Type	Sine wave
Harmonic distortion	Less than 2%
Crest factor	3:1
Bypass type	Internal Bypass (Automatic and Manual)

Conformance

Product Certifications	CE	
	EAC	
	IRAM	
	RCM	
	VDE	
marking	CE Mark	
Standards	EN/IEC 62040-1:2019/A11:2021	
	EN/IEC 62040-2:2006/AC:2006	
	EN/IEC 62040-2:2018	

Environmental

Ambient Air Temperature for Operation	32104 °F (040 °C)
Relative Humidity	095 %
Operating altitude	010000 ft
Ambient Air Temperature for Storage	5113 °F (-1545 °C)
Storage Relative Humidity	095 % non-condensing
Storage altitude	050000 ft (0.000000000015240.0000000000 m)
acoustic level	55 dBA
Online Thermal Dissipation	1947 Btu/h
IP degree of protection	IP20

Communications & Management

Free slots	1
Pre-Installed SmartSlot™ Cards	Network management card 3 with environmental monitoring
Alarm	Audible and visible alarms : prioritized by severity
Emergency Power Off (EPO)	Yes

Surge Protection and Filtering

Surge energy rating 480

Ordering and shipping details

GTIN	731304304272
Country of origin	PH

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	18.1 in (46.1 cm)
Package 1 Width	23.6 in (60 cm)
Package 1 Length	39.4 in (100 cm)
Package 1 Weight	279.004 lb(US) (126.554 kg)

Contractual warranty

Warranty 3 years repair or replace (excluding battery) and 2 years for battery



Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO2 products.

Learn more about Green Premium >









Energy Efficient Take-back Transparency RoHS/REACh

Resource performance

Energy Efficient Product



Take-Back Program Available

Well-being performance



Rohs Exemption Information

Certifications & Standards

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant with Exemptions
China Rohs Regulation	China RoHS declaration
	Product out of China RoHS scope. Substance declaration for your information.
Environmental Disclosure	Product Environmental Profile
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.
Circularity Profile	End of Life Information
California Proposition 65	"WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov"

Product data sheet

SRT10KXLI

Image of product / Alternate images

Alternative





