



Overview

Lead time	Usually in Stock
-----------	------------------

General

Provided equipment	CD with software Communication cable Documentation CD Installation guide Removable support feet USB cable Warranty card
--------------------	---

Physical

Number of rack unit	3U
Colour	Black
Depth	59 cm
Height	12.8 cm
Net weight	30.53 kg
Width	43.2 cm

Input

Network frequency	40...70 Hz auto-sensing
Plug standard	IEC 60320 C14
Input voltage limits	50...150 V 40% load 80...150 V
Inputvolt_other	220 V 240 V
Input voltage	230 V

Output

Rated power in W	900 W
Maximum configurable power in W	900 W
Harmonic distortion	Less than 2 %
Output frequency	50/60 Hz +/- 3 Hz sync to mains

Outputvolt_other	220 V 240 V
Crest factor	3 : 1
UPS type	Double conversion online
Wave type	Sine wave
Nb of power socket outlets	8 IEC 60320 C13
Bypass type	Built-in bypass
Output voltage	230 V

Conformance

Product certifications	CE EAC RCM VDE
Marking	CE Mark

Environmental

Ambient air temperature for operation	0...40 °C
Relative humidity	0...95 % non-condensing
Operating altitude	0...10000 ft
Ambient air temperature for storage	-15...45 °C
Storage altitude	0.00...15240.00 m
Acoustic level	50 dBA
Heat dissipation	400 Btu/h
IP degree of protection	IP20

Batteries & Runtime

Battery type	Li-Ion (Lithium-Ion)
Number of battery filled slots	0
Number of battery free slots	0
Battery recharge time	6 h
Liquid value	0
Battery voltage	48 V

Communications & Management

Free slots	1
Control panel	Multifunction LCD status and control console
Alarm	Audible and visible alarms prioritized by severity
Emergency power off	Yes

Surge Protection and Filtering

Surge energy rate	340 J
-------------------	-------

Packing Units

Package 1 Weight	46.86 kg
Package 1 Height	44.5 cm
Package 1 width	60 cm
Package 1 Length	85 cm
Number of Units in Package 3	6

Offer Sustainability

EU RoHS Directive	Compliant
-------------------	-----------

EU RoHS Declaration

Mercury free	Yes
RoHS exemption information	Yes

Contractual warranty

Warranty	5 year repair or replace
----------	--------------------------