

4MP Fixed-focal Wi-Fi Turret Network Camera

DH-T4A-LED



Series Overview

The Turret Series, which is under the Dahua Wireless series, are cameras that are not only easy to install and operate, but also perform outstandingly and are cost-effective. They capture sharp, detailed images of scenes in high definition and offer powerful functions, such as AI human detection, to accurately trigger alarms. Information is also synchronously sent to your phone to keep you up-to-date. With its IP67 rating, these cameras are able to withstand harsh environments, making them highly suitable for use in small and medium-sized settings such as small-sized retail stores.



4MP

Clear images with sharp details



Al Human Detection

Focuses on what matters and reduces false alarms



Full-color

Captures full-color details



Built-in Mic

Provides traceable audio details



IP67 Protection

Withstands harsh environments



H.265

Advanced H.265 compression technology



DMSS App

Easy to use



Micro SD Card

Low-cost storage



Upgrade Your Experience with DMSS

Dahua Mobile Security Surveillance (DMSS) is a professional remote surveillance management platform that offers remote monitoring, device migration, and sharing. When connected to the internet, the platform provides real-time alerts to improve surveillance efficiency and grant flexibility in security management.









Specifications

Camera

1/3" CMOS Image Sensor

Max. Resolution 2560 (H) × 1440 (V)

Auto/Manual 1/3 s-1/100,000 s Electronic Shutter Speed Up to 30 m (98.53 ft) (Warm light) Illumination Distance

Illuminator On/Off Control

Illuminator Number 2 (Warm light)

Max. Aperture

2.8 mm: H: 98°; V: 55°; D: 115° 3.6 mm: H: 78°; V: 41°; D: 94° Field of View

Intelligence

Support the classification and accurate detection of Human Detection

human

Video & Audio

Video Compression H.264B; H.264; H.264H; H.265

Main stream: 2560 × 1440@(1-25/30 fps); sub stream: 640 × 480@(1–25/30 fps); *The values above are the max. frame rates of each Video Frame Rate

stream; for multiple streams, the values will be subjected to the total encoding capacity.

4M (2560 × 1440); 3M (2304 × 1296); 1080p (1920 × Resolution 1080); 1.3M (1280 × 960); 720p (1280 × 720)

H.264: 32kbps ~ 4096kbps H.265: 12kbps ~ 4096kbps Video Bit Rate

Color/B/W Day/Night OFF/ON Motion Detection

Smart Illumination Yes

0°/180° Image Rotation

Built-in MIC Yes, built-in Mic

Audio Compression G.711a; G.711Mu; PCM; G.726

Network

Network Port RJ-45 (10/100 Base-T)

IEEE 802.11b/g/n 2.4–2.4835 GHz, 2.4 G.≤20dBm@2400-2483.5MHz Wi-Fi

Storage Micro SD card (support max. 256 GB)

Smart PSS; DSS; DMSS Management Software

Mobile Client iOS;Android

General

CE-LVD: EN62368-1;

CE-EMC: Electromagnetic Compatibility Directive Certifications

CE-RED: Radio Equipment Directive 2014/53/EU

12 VDC **Power Supply**

Basic: 2.2 W (12 VDC) Power Consumption

Max. (H.265+warm light intensity): 6.2 W (12 VDC)

-40 °C to +60 °C (-40 °F to +140 °F) Operating Temperature

<95% Operating Humidity Protection

Inner core: Metal + Plastic Casing Material

Cover: Plastic

Product Dimensions Φ 109.9 mm × 102.2 mm (Φ 4.33" × 4.02")

323 g (0.71 lb) Net Weight

What's in the box



Tools:

Installation Position

Map×1

Mounting Plate×1 Screw Package×1

Waterproof Connector x 1

Power Adapter×1 OR Codex1 Quick Start Guide×1

Legal and Regulation Information×1

Documents:

Power:



