


User's Manual



5-Port 10/100/1000T VPN Security Router

► VR-100



Copyright

Copyright (C) 2019 PLANET Technology Corp. All rights reserved.

The products and programs described in this User's Manual are licensed products of PLANET Technology. This User's Manual contains proprietary information protected by copyright, and this User's Manual and all accompanying hardware, software, and documentation are copyrighted.

No part of this User's Manual may be copied, photocopied, reproduced, translated, or reduced to any electronic medium or machine-readable form by any means, electronic or mechanical including photocopying, recording, or information storage and retrieval systems, for any purpose other than the purchaser's personal use, and without the prior express written permission of PLANET Technology.

Disclaimer

PLANET Technology does not warrant that the hardware will work properly in all environments and applications, and makes no warranty and representation, either implied or expressed, with respect to the quality, performance, merchantability, or fitness for a particular purpose.

PLANET has made every effort to ensure that this User's Manual is accurate; PLANET disclaims liability for any inaccuracies or omissions that may have occurred. Information in this User's Manual is subject to change without notice and does not represent a commitment on the part of PLANET.

PLANET assumes no responsibility for any inaccuracies that may be contained in this User's Manual. PLANET makes no commitment to update or keep current the information in this User's Manual, and reserves the right to make improvements and/or changes to this User's Manual at any time without notice.

If you find information in this manual that is incorrect, misleading, or incomplete, we would appreciate your comments and suggestions.

FCC Compliance Statement

This Equipment has been tested and found to comply with the limits for a Class A digital device, pursuant to Part 15 of the FCC rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications.

However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

- Reorient or relocate the receiving antenna.
- Increase the separation between the equipment and receiver.
- Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
- Consult the dealer or an experienced radio/TV technician for help.

CE mark Warning



The is a class A device, In a domestic environment, this product may cause radio interference, in which case the user may be required to take adequate measures.

WEEE



To avoid the potential effects on the environment and human health as a result of the presence of hazardous substances in electrical and electronic equipment, end users of electrical and electronic equipment should understand the meaning of the crossed-out wheeled bin symbol. Do not dispose of WEEE as unsorted municipal waste and have to collect such WEEE separately.

Trademarks

The PLANET logo is a trademark of PLANET Technology. This documentation may refer to numerous hardware and software products by their trade names. In most, if not all cases, these designations are claimed as trademarks or registered trademarks by their respective companies.

Revision

User's Manual of PLANET 5-Port 10/100/1000T VPN Security Router

Model: VR-100

Rev.: 1.0 (September, 2019)

Part No. EM-VR-100_v1.0

Table of Contents

| | | |
|------------|-------------------------------------|----|
| Chapter 1. | Product Introduction..... | 6 |
| 1.1 | Package Contents..... | 6 |
| 1.2 | Overview | 6 |
| 1.3 | Topology..... | 10 |
| 1.4 | Features | 11 |
| 1.5 | Product Specifications | 13 |
| Chapter 2. | Hardware Introduction | 15 |
| 2.1 | Physical Descriptions..... | 15 |
| 2.1.1 | Front View..... | 15 |
| 2.1.2 | Rear View | 15 |
| 2.1.3 | Diagrams..... | 16 |
| 2.2 | Hardware Installation | 17 |
| 2.2.1 | Desktop Installation | 17 |
| 2.2.2 | Rack Mounting (optional)..... | 17 |
| Chapter 3. | Preparation | 20 |
| 3.1 | Requirements..... | 20 |
| 3.2 | Setting TCP/IP on your PC | 21 |
| 3.2.1 | Windows 7/8 | 21 |
| 3.2.2 | Windows 10 | 25 |
| 3.3 | Planet Smart Discovery Utility..... | 28 |
| Chapter 4. | Web-based Management | 30 |
| 4.1 | Introduction | 30 |
| 4.2 | Logging in to the VPN Router | 30 |
| 4.3 | Main Web Page..... | 31 |
| 4.4 | System | 33 |
| 4.4.1 | Wizard..... | 34 |
| 4.4.2 | Dashboard | 40 |
| 4.4.3 | Status..... | 41 |
| 4.4.4 | Statistics..... | 42 |
| 4.4.5 | Connection Status | 42 |
| 4.4.6 | SNMP..... | 43 |
| 4.5 | Network..... | 44 |
| 4.5.1 | WAN..... | 45 |
| 4.5.2 | WAN Advanced..... | 46 |

| | | |
|------------------------------------|---------------------------------|----|
| 4.5.3 | LAN Setup..... | 47 |
| 4.5.4 | Routing..... | 48 |
| 4.5.5 | WAN IPv6 Setting | 50 |
| 4.5.6 | DHCP | 50 |
| 4.5.7 | DDNS | 52 |
| 4.5.8 | MAC Address Clone | 54 |
| 4.6 | Security | 55 |
| 4.6.1 | Firewall..... | 56 |
| 4.6.2 | MAC Filtering | 58 |
| 4.6.3 | IP Filtering..... | 59 |
| 4.6.4 | Web Filtering..... | 60 |
| 4.6.5 | Port Forwarding | 61 |
| 4.6.6 | DMZ | 62 |
| 4.7 | VPN 64 | |
| 4.6.7 | IPsec..... | 65 |
| 4.6.8 | GRE | 68 |
| 4.6.9 | PPTP Server | 70 |
| 4.6.10 | L2TP Server..... | 72 |
| 4.6.11 | SSL VPN | 74 |
| 4.6.12 | VPN Connection | 75 |
| 4.7 | Maintenance..... | 76 |
| 4.7.1 | Administrator..... | 76 |
| 4.7.2 | Date and Time | 77 |
| 4.7.3 | Save/Restore Configuration..... | 78 |
| 4.7.4 | Upgrading Firmware | 79 |
| 4.7.5 | Reboot / Reset | 79 |
| 4.7.6 | Diagnostics | 80 |
| Appendix A: DDNS Application | | 82 |

Chapter 1. Product Introduction

1.1 Package Contents

The package should contain the following:

- VR-100 x 1
- Quick Installation Guide x 1
- Power Cord x 1
- Feet Pads x 4



If any of the above items are missing, please contact your dealer immediately.

1.2 Overview

Powerful VPN Security Solution

The innovation of the Internet has created tremendous worldwide opportunities for e-business and information sharing. It has become essential for businesses to focus more on network security issues. The demand for information security has become the primary concern for the enterprises. To fulfill this demand, PLANET has launched the VR-100 VPN Security Router, an all-in-one appliance that carries several main categories across your network security deployments: SPI firewall security protection, policy auditing (Content Filtering, VPN Tunnel and MAC/IP Filtering), and easy management (Setup Wizard, DHCP Server and Dashboard). Furthermore, its Dual-WAN Failover and Outbound Load Balance features can improve the network efficiency while the web-based interface provides friendly and consistent user experience.




Powerful VPN Security Solution

The innovation of the Internet has created tremendous worldwide opportunities for e-business and information sharing. It has become essential for businesses to focus more on network security issues. The demand for information security has become the primary concern for the enterprises. To fulfill this demand, PLANET has launched the VR-100 VPN Security Router, an all-in-one appliance that carries several main categories across your network security deployments: SPI firewall security protection, policy auditing (Content Filtering, VPN Tunnel and MAC/IP Filtering), and easy management (Setup Wizard, DHCP Server and Dashboard). Furthermore, its Dual-WAN Failover and Outbound Load Balance features can improve the network efficiency while the web-based interface provides friendly and consistent user experience.

Excellent Ability in Threat Defense


The VR-100 built-in SPI (Stateful Packet Inspection) firewall and Blocking DoS/DDoS attack functions provide high efficiency and extensive protection for your network. Virtual Server and DMZ functions can let you setup servers in the Intranet and still provide services to the Internet users.



Ideal VPN Security Router Solution for SMBs

The VR-100 provides complete data security and privacy for accessing and exchanging most sensitive data, built-in IPSec VPN function with DES/3DES/AES encryption and MD5/SHA-1/SHA-256/SHA-384/SHA-512 authentication, and GRE, SSL, PPTP and L2TP server mechanism. The full VPN capability in the VR-100 makes the connection solid secure, more flexible, and more capable.

The VR-100 supports many popular security features including Content Filtering to block specific URL, MAC/IP filtering, outbound load-balancing and more. Furthermore, it provides higher performance with all Gigabit Ethernet interfaces which offer faster speeds for your network applications. The Gigabit user-defined interfaces flexibly fulfill the network requirement nowadays, and the Dual-WAN interfaces enable the VR-100 to support outbound load balancing and WAN fail-over features.



Cybersecurity Network Solution to Minimize Security Risks


The cybersecurity feature included to protect the switch management in a mission-critical network virtually needs no effort and cost to install. For efficient management, the VR-100 is equipped with HTTPS web and SNMP management interfaces. With the built-in web-based management interface, the VR-100 offers an easy-to-use, platform independent management and configuration facility. The VR-100 supports SNMP and it can be managed via any management software based on the standard SNMP protocol.

Improving Network Efficiency

The VR-100 has link redundancy, Content Filtering and many more functions to make the entire network system better. It is applicable to the small-scale sector (from 10 to 50 people), using a 9-inch desktop design, with five Gigabit ports (WAN/LAN). The VR-100's economical price with complete cable management features make it an inevitable choice for the next-generation office network load balancer.

The VR-100's built-in Content Filtering feature can automatically resolve the IP address corresponding to all. Users' network can be easily managed by just typing the URL of the websites like Facebook, YouTube and Yahoo.


The VR-100 can connect dual WANs with up to two different ISPs. It creates a stable and qualified VPN connection for many important applications such as VoIP, video conferencing and data transmission.



1.3 Topology

PLANET VR-100 VPN security router has an SPI firewall with DoS detection. Through the Content Filtering function, it can easily block the websites like Facebook, YouTube, Gmail, etc. With IPSec/GRE/PPTP/L2TP/SSL VPN solutions, the VR-100 provides secured data communication for branches, vendors, and mobile workers with a flexible way to connect back to the headquarters.

The VR-100 connects dual WANs with up to two different ISPs. It creates a stable and qualified VPN connection for many important applications such as VoIP, video conferencing and data transmission.



1.4 Features

➤ Hardware

- 5 10/100/1000BASE-T RJ45 ports
- 1 undefined Ethernet port (LAN/WAN)
- Dual-WAN function
- 1 USB 3.0 port for system configuration backup and restore
- Reset button
- Desktop installation or rack mounting (optional)
- Fanless design

➤ IP Routing Feature

- Static Route
- Dynamic Route

➤ Firewall Security

- Stateful Packet Inspection (SPI) firewall
- Blocks DoS/DDoS attack
- Content filtering
- MAC/IP filtering
- Blocks SYN/ICMP flooding

➤ VPN Features

- IPSec (Host to Host)/GRE/PPTP server/L2TP/SSL(Open VPN)
- Max. Connection Tunnel Entries: 60 VPN tunnels,
- Encryption methods: DES, 3DES, AES, AES-128/192/256
- Authentication methods: MD5, SHA-1, SHA-256, SHA-384, SHA-512

➤ Networking

- Outbound load balancing
- Failover for dual-WAN
- Static IP/DHCP client for WAN
- Protocols: TCP/IP, UDP, ARP, IPv4, IPv6
- Port forwarding
- DMZ
- SNMP
- DHCP server/NTP client

- MAC address clone
- DDNS: PLANET DDNS, PLANET Easy DDNS, DynDNS and No-IP
- Cybersecurity

➤ **Others**

- Setup wizard
- Dashboard for real time system overview
- Supported access by HTTP or HTTPS
- Auto reboot
- PLANET Smart Discovery utility/UNI-NMS supported

1.5 Product Specifications


| | |
|--------------------------------|---|
| Product | VPN security router |
| Model | VR-100 |
| Hardware | |
| Ethernet | 5 10/100/1000BASE-T RJ45 Ethernet ports including <ul style="list-style-type: none"> ■ 3 LAN ports ■ 1 WAN port ■ 1 LAN/WAN port |
| USB Port | 1 USB 3.0 port for system configuration backup and restore |
| Reset Button | Reset to factory default |
| Thermal Fan | Fanless |
| LED Indicators | PWR (Green) Internet (Green) LAN/WAN (Green) |
| Installation | Desktop installation or rack mounting (optional) |
| Power Requirements | 100-240V AC, 1A max. |
| Power Consumption | 13W max. |
| Weight | 0.85kg |
| Dimensions (W x D x H) | 215.2 x 135 x 42.6 mm |
| Software | |
| Management | Web browser |
| Operation Mode | Routing mode |
| Routing Protocol | Static route: 32 Dynamic route: 4096 |
| NAT Throughput | Max. 900Mbps |
| Firewall Security | Stateful packet inspection (SPI) Blocks DoS/DDoS attack |
| Outbound Load Balancing | Supported algorithms: Weight |
| Protocol | IPv4, IPv6, TCP/IP, UDP, ARP, HTTP, HTTPS, NTP, DNS, PLANET DDNS, PLANET Easy DDNS, DHCP, SNMP, |
| Content Filtering | MAC filtering IP filtering Web filtering |
| Log | System Operation Log |

| | |
|-----------------------------------|---|
| Others | Outbound load balancing Failover for dual-WAN Port forwarding DMZ Cybersecurity Dashboard Setup wizard Auto reboot PLANET Smart Discovery utility/UNI-NMS supported |
| VPN | |
| VPN Function | <ul style="list-style-type: none"> ■ IPSec (Host to Host) ■ GRE ■ PPTP server ■ L2TP ■ SSL (Open VPN) |
| VPN Tunnels | Max. 60 |
| VPN Throughput | Max. 60Mbps |
| Encryption Methods | DES, 3DES, AES or AES-128/192/256 encrypting |
| Authentication Methods | MD5/SHA-1/SHA-256/SHA-384/SHA-512 authentication algorithm |
| Standards Conformance | |
| Regulatory Compliance | CE, FCC |
| Environment Specifications | |
| Operating | Temperature: 0 ~ 50 degrees C Relative Humidity: 5 ~ 95% (non-condensing) |
| Storage | Temperature: -10 ~ 60 degrees C Relative Humidity: 5 ~ 95% (non-condensing) |
| Standard Accessories | |
| Packet Contents | <ul style="list-style-type: none"> ■ VR-100 x 1 ■ Quick Installation Guide x 1 ■ Power Cord x 1 ■ Feet Pads x 4 |

Chapter 2. Hardware Introduction

2.1 Physical Descriptions

2.1.1 Front View



| LED | | |
|--------------|---|---|
| PWR | Green | Lights up when the power is on. |
| Internet | | Lights up when the router connects to internet successfully. |
| Port 1-5 | | “Steady on” indicates the port is connected to other network device. “Blink” to indicate there is traffic on the port. |
| Ports | | |
| USB Port | USB 3.0 port for system configuration backup and restoration. | |
| Reset Button | Power on the device and press the reset button for ten seconds to restore it to factory default settings. | |
| Port 1-3 | It is a LAN port for connecting to a switch. | |
| Port 4 | Default is LAN port. It can be defined as LAN port or WAN port. | |
| Port 5 | It is a WAN port for connecting to a perimeter router. | |


2.1.2 Rear View



| Interface | |
|---------------------|--|
| AC Power Receptacle | For compatibility with electrical outlet standard in most areas of the world, the device's power supply automatically adjusts to line power in the range of 100-240V AC and 50/60Hz. Plug the female end of the power cord firmly into the receptacle on the rear |

panel of the device and the other end into an electrical outlet, and the power will be ready.

2.1.3 Diagrams



Unit: mm

2.2 Hardware Installation

2.2.1 Desktop Installation

To install the VR-100 on desktop, simply follow the following steps:

Step 1: Place the device on desktop.

Step 2: Keep enough ventilation space between the device and the surrounding objects.



When choosing a location, please keep in mind the environmental restrictions should be under the specifications of the VR-100.

Step 3: Connect your device to hub / switch.

A. Connect one end of a standard network cable to the LAN port (port 1) of the device.

B. Connect the other end of the cable to the hub / switch.



The UTP Category 5, 5e or 6 network cabling with RJ45 tips is recommended.

Step 4: Connect your device to internet.

A. Connect one end of a standard network cable to the WAN port (port 5) of the device.

B. Connect the other end of the cable to the LAN port of ISP network device (such as a modem).



If there is only one line connected to the outer network in your network environment, it is suggested that you use WAN port (port 5).

Step 5: Power on the device. When the device receives power, the Power LED should remain solid Green.

2.2.2 Rack Mounting (optional)


If you need install the VR-100 in a 19-inch standard rack, please contact with your dealer first and order the accessories -- **RKE-10B**, it is a rack mount kits and not included in the package.

Please follow the instructions described below.

(The device shown on this chapter is just a representation of the said device.)

Step 1: Place your device on a hard flat surface, with the front panel positioned towards your front side.

Step 2: Attach a rack-mount bracket to each side of the device with supplied screws attached to the package. In the picture below, it shows how to attach brackets to one side of the device.




You must use the screws supplied with the mounting brackets. Damage caused to the parts by using incorrect screws would invalidate the warranty.

Step 3: Secure the brackets tightly.

Step 4: Follow the same steps to attach the second bracket to the opposite side.

Step 5: After the brackets are attached to the device, use suitable screws to securely attach the brackets to the rack, as shown in the picture below.



The width of the rack should be at least 453 mm.

Step 6: Proceed with Steps 4 and 5 6 of session 2.2.1 Desktop Installation to connect the network cabling and power on the device.

Chapter 3. Preparation

Before getting into the device's web UI, user has to check the network setting and configure PC's IP address.

3.1 Requirements

User is able to confirm the following items before configuration:

1. Please confirm the network is working properly; it is strongly suggested to test your network connection by connecting your computer directly to ISP.
2. Suggested operating systems: Windows 7 / 8 / 10.
3. Recommended web browsers: IE / Firefox / Chrome.

3.2 Setting TCP/IP on your PC

The default IP address of the VR-100 is 192.168.1.1, and the DHCP Server is on.


Please set the IP address of the connected PC as DHCP client, and the PC will get IP address automatically from the VR-100.

Please refer to the following to set the IP address of the connected PC.


3.2.1 Windows 7/8

If you are using Windows 7/8, please refer to the following:


1. Click on the network icon from the right side of the taskbar and then click on “Open Network and Sharing Center”.




2. Click **"Change adapter settings"**.




3. Right-click on the Local Area Connection and select Properties.



4. Select Internet Protocol Version 4 (TCP/IPv4) and click Properties or directly double-click on Internet Protocol Version 4 (TCP/IPv4).




5. Select **"Use the following IP address"** and **"Obtain DNS server address automatically"**, and then click the **"OK"** button.




3.2.2 Windows 10

If you are using Windows 10, please refer to the following:


1. In the search box on the taskbar, type “View network connections”, and then select View network connections at the top of the list.




2. Right-click on the Local Area Connection and select Properties.



3. Select Internet Protocol Version 4 (TCP/IPv4) and click Properties or directly double-click on Internet Protocol Version 4 (TCP/IPv4).



4. Select **"Use the following IP address"** and **"Obtain DNS server address automatically"**, and then click the **"OK"** button.



3.3 Planet Smart Discovery Utility

For easily listing the router in your Ethernet environment, the search tool -- Planet Smart Discovery Utility is an ideal solution.

The following installation instructions are to guide you to running the Planet Smart Discovery Utility.

1. Deposit the Planet Smart Discovery Utility in administrator PC.
2. Run this utility as the following screen appears.




Figure 3-1-6: Planet Smart Discovery Utility Screen



If there are two LAN cards or above in the same administrator PC, choose a different LAN card by using the “**Select Adapter**” tool.

3. Press the “**Refresh**” button for the currently connected devices in the discovery list as the screen shows below:




Figure 3-1-7: Planet Smart Discovery Utility Screen

1. This utility shows all necessary information from the devices, such as MAC address, device name, firmware version, and device IP subnet address. It can also assign new password, IP subnet address and description to the devices.
2. After setup is completed, press the “**Update Device**”, “**Update Multi**” or “**Update All**” button to take effect. The functions of the 3 buttons above are shown below:
 - **Update Device:** use current setting on one single device.
 - **Update Multi:** use current setting on choose multi-devices.
 - **Update All:** use current setting on whole devices in the list.The same functions mentioned above also can be found in “**Option**” tools bar.
3. To click the “**Control Packet Force Broadcast**” function, it allows you to assign a new setting value to the device under a different IP subnet address.
4. Press the “**Connect to Device**” button and the Web login screen appears.

Press the “**Exit**” button to shut down the Planet Smart Discovery Utility.

Chapter 4. Web-based Management

This chapter provides setup details of the device's Web-based Interface.

4.1 Introduction

The device can be configured with your Web browser. Before configuring, please make sure your PC is under the same IP segment with the device.

4.2 Logging in to the VPN Router

Then refer to the steps to configure the VPN router:

- Step 1.** Connect the IT administrator's PC and VPN router's LAN port (port 1) to the same hub / switch, and then launch a browser to link the management interface address which is set to **http://192.168.1.1** by default.



The DHCP server of the VPN router is enabled. Therefore, the LAN PC will get IP from the VPN router. If user needs to set IP address of LAN PC manually, please set the IP address within the range between 192.168.1.2 and 192.168.1.254 inclusively, and assigned the subnet mask of 255.255.255.0.

- Step 2.** The browser prompts you for the login credentials. (Both are “**admin**” by default.)

Default IP address: **192.168.1.1**

Default user name: **admin**

Default password: **admin**



Administrators are strongly suggested to change the default admin and password to ensure system security.

4.3 Main Web Page

After a successful login, the main web page appears. The web main page displays the web panel, main menu, function menu, and the main information in the center.




Figure 4-: Main Web Page

■ Web Panel

The web panel displays an image of the device's ports as shown in Figure 4-2.




Figure 4-2: Web Panel

| Object | Icon | Function |
|--------|------|---|
| LAN | | To indicate the LAN with the RJ45 plug-in. |
| | | To indicates network data is sending or receiving |

■ Main Menu

The main menu displays the product name, function menu, and main information in the center. Via the Web management, the administrator can set up the device by selecting the functions those listed in the function menu and button as shown in [Figures 4-3 and 4-4](#).





Figure 4-3: Function Menu

| Object | Description |
|--------------------|--|
| System | Provides System information of the router. |
| Network | Provides WAN, LAN and network configuration of the router. |
| Security | Provides Firewall and security configuration of the router. |
| VPN | Provides VPN configuration of the router. |
| Maintenance | Provides firmware upgrade and setting file restore/backup configuration of the router. |



Figure 4-4: Function Button

| Object | Description |
|---|---|
|  | Click the " Refresh button " to refresh the current web page. |
|  | Click the " Logout button " to log out the web UI of the router. |

4.4 System

Use the System menu items to display and configure basic administrative details of the router. The System menu shown in [Figure 4-5](#) provides the following features to configure and monitor system.




Figure 4-5: System Menu

| Object | Description |
|--------------------------|--|
| Wizard | The Wizard will guide the user to configuring the router easily and quickly. |
| Dashboard | The overview of system information includes connection, port, and system status. |
| Status | Display the status of the system, LAN and WAN. |
| Statistics | Display statistics information of network traffic of LAN and WAN. |
| Connection Status | Display the DHCP client table and the ARP table. |
| SNMP | Display SNMP system information. |

4.4.1 Wizard

The Wizard will guide the user to configuring the router easily and quickly. There are different procedures in different operation modes. According to the operation mode you switch to, please follow the instructions below to configure the router via **Setup Wizard** as shown in [Figure 4-6](#).




Figure 4-6: Setup Wizard

Step 1: LAN Interface

Set up the IP Address and Subnet Mask for the LAN interface as shown in [Figure 4-7](#).





Figure 4-7: Setup Wizard – LAN Configuration

| Object | Description |
|--------------------|---|
| IP Address | Enter the IP address of your router. The default is 192.168.1.1. |
| Subnet Mask | An address code that determines the size of the network. Normally use 255.255.255.0 as the subnet mask. |
| DHCP Server | By default, the DHCP Server is enabled. If user needs to disable the function, please uncheck the box. |

| | |
|---------------------------|--|
| Start IP Address | By default, the start IP address is 192.168.1.100. Please do not set it the same as the IP address of the router. |
| Maximum DHCP Users | By default, the Maximum DHCP Users is 101. It means the router will provide DHCP client with IP address from 192.168.1.100 to 192.168.1.200 when the start IP address is 192.168.1.100. |
| Next | Press this button to next step. |
| Cancel | Press this button to undo any changes made locally and revert to previously saved values. |

Step 2: WAN Interface

The router supports two access modes in the WAN side is shown in [Figure 4-8](#)



STEP 2 - Network Interface WAN

1 LAN 2 WAN 3 Security Settings 4 Setup Completed

WAN1 WAN2

Connection Type

IP Address

Netmask

Default Gateway

DNS Server 1

DNS Server 2

Cancel Previous Next

Figure 4-8: Setup Wizard – WAN 1 Configuration




Figure 4-9: Setup Wizard – WAN 2 Configurations

Mode 1 - Static IP

Select **Static IP Address** if all the Internet port's IP information is provided to you by your ISP. You will need to enter the **IP Address**, **Netmask**, **Default Gateway**, and **DNS Server** provided to you by your ISP. Each IP address entered in the fields must be in the appropriate IP form, which are four octets separated by a dot (x.x.x.x). The router will not accept the IP address if it is not in this format. The setup is shown in [Figure 4-10](#).





Figure 4-10: WAN Interface Setup – Static IP Setup

| Object | Description |
|------------------------|--|
| IP Address | Enter the IP address assigned by your ISP. |
| Netmask | Enter the Netmask assigned by your ISP. |
| Default Gateway | Enter the Gateway assigned by your ISP. |
| DNS Server | The DNS server information will be supplied by your ISP. |

| | |
|-----------------|---|
| Next | Press this button to next step. |
| Previous | Press this button to previous step. |
| Cancel | Press this button to undo any changes made locally and revert to previously saved values. |

Mode 2 - DHCP Client

Select DHCP Client to obtain IP Address information automatically from your ISP. The setup is shown in Figure 4-11.




The screenshot shows the WAN1 configuration tab. The 'Connection Type' is set to 'DHCP'. Below this, there are input fields for 'IP Address', 'Netmask', 'Default Gateway', 'DNS Server 1', and 'DNS Server 2', all of which are currently empty.

Figure 4-11: WAN Interface Setup – DHCP Setup

Step 3: Security Setting

Set up the Security Settings as shown in Figure 4-12.



The screenshot shows the 'STEP 3 - Security Settings' screen. At the top, a progress bar indicates four steps: 1 LAN, 2 WAN, 3 Security Settings (current), and 4 Setup Completed. Below the progress bar, there are five security settings, each with 'Enable' and 'Disable' radio buttons:

- SPI Firewall: ☒ Enable ☐ Disable
- Block SYN Flood: ☒ Enable ☐ Disable
- Block ICMP Flood: ☐ Enable ☒ Disable
- Block WAN Ping: ☐ Enable ☒ Disable
- Remote Management: ☐ Enable ☒ Disable

At the bottom right, there are three buttons: 'Cancel', 'Previous', and 'Next'.

Figure 4-12: Setup Wizard –Security Setting

| Object | Description |
|--------------------------|--|
| SPI Firewall | The SPI Firewall prevents attack and improper access to network resources. The default configuration is enabled. |
| Block SYN Flood | SYN Flood is a popular attack way. DoS and DDoS are TCP protocols. Hackers like using this method to make a counterfeit of connection, and the CPU and memory, and so on. The default configuration is enabled. |
| Block ICMP Flood | ICMP is kind of a pack of TCP/IP; its important function is to transfer simple signal on the Internet. There are two normal attack ways which hackers like to use, Ping of Death and Smurf attack. The default configuration is disabled. |
| Block WAN Ping | Enable the function to allow the Ping access from the Internet network. The default configuration is disabled. |
| Remote Management | Enable the function to allow the web server access of the router from the Internet network. The default configuration is disabled. |
| Next | Press this button to next step. |
| Previous | Press this button to previous step. |
| Cancel | Press this button to undo any changes made locally and revert to previously saved values. |

Step 4: Setup Completed

The page will show the summary of LAN, WAN and Security settings as shown in [Figure 4-13](#).

STEP 4 - Setup Completed

1

LAN

2

WAN

3

Security Settings

4

Setup Completed

LAN

Enable: Static

IP: 192.168.1.1 / 255.255.255.0

WAN1

Enable: DHCP

WAN2

Enable: OFF

Security Settings

SPI Firewall: ON

Block SYN Flood: ON

Block ICMP Flood: OFF

Block WAN Ping: OFF

Remote Management: OFF

Previous

Finish

Figure 4-13: Setup Wizard –Setup Completed

| Object | Description |
|-----------------|--|
| Finish | Press this button to save and apply changes. |
| Previous | Press this button to previous step. |

4.4.2 Dashboard

The dashboard provides an overview of system information including connection, port, and system status as shown in Figure 4-14.







Figure 4-14: Dashboard

WAN/LAN Connection Status

| Object | Description |
|--------|--|
| | The status means WAN is connected to Internet and LAN is connected. |
| | The status means WAN is disconnected to Internet and LAN is connected. |
| | The status means WAN is connected to Internet and LAN is disconnected. |

Port Status

| Object | Description |
|--------|--------------------------|
| | Ethernet port is in use. |

| | |
|---|------------------------------|
|  | Ethernet port is not in use. |
|  | USB port is in use. |
|  | USB port is not in use. |

System Information

| Object | Description |
|--------|--------------------------|
| CPU | Display the CPU loading |
| Memory | Display the memory usage |

4.4.3 Status

This page displays system information as shown in [Figure 4-15](#).

| Router Information | |
|-----------------------|-------------------------|
| Model Name | VR-100 |
| Firmware Version | v1.1806b190904 |
| Current Time | 2019-01-30 Wed 20:21:45 |
| Running Time | 0d 00:00:57 |
| WAN1 | |
| MAC Address | A8:F7:E0:00:06:62 |
| Connection Type | DHCP |
| IP Address | 192.168.1.189 |
| Subnet Mask | 255.255.255.0 |
| Gateway | 192.168.1.254 |
| LAN | |
| MAC Address | A8:F7:E0:00:06:61 |
| IP Address | 192.168.1.1 |
| Subnet Mask | 255.255.255.0 |
| DHCP Service | Enable |
| DHCP Start IP Address | 192.168.1.100 |
| DHCP End IP Address | 192.168.1.200 |
| Max DHCP Clients | 101 |

Figure 4-15: Status

4.4.4 Statistics

This page displays the number of packet that pass through the router on the WAN and LAN. The statistics are shown in [Figure 4-16](#).

| WAN1 | |
|------------------|--------|
| Sent Packets | 223 |
| Sent Bytes | 198984 |
| Received Packets | 2008 |
| Received Bytes | 385555 |

| LAN | |
|------------------|-------|
| Sent Packets | 7 |
| Sent Bytes | 746 |
| Received Packets | 221 |
| Received Bytes | 15363 |

Figure 4-16: Statistics

4.4.5 Connection Status

The page will show the DHCP Table and ARP Table. .

| DHCP Table | | | |
|------------|------------|-------------|-----------------|
| Name | IP Address | MAC Address | Expiration Time |

| ARP Table | | | |
|----------------|-------------------|----------|--|
| IP Address | MAC Address | ARP Type | |
| 8.8.8.8 | 00:00:00:00:00:00 | unknow | |
| 208.67.222.222 | 00:00:00:00:00:00 | unknow | |
| 8.8.8.8 | 00:00:00:00:00:00 | unknow | |
| 208.67.222.222 | 00:00:00:00:00:00 | unknow | |
| 192.168.1.18 | 00:00:00:00:00:00 | unknow | |
| 192.168.1.69 | 00:30:11:11:11:12 | dynamic | |
| 192.168.1.69 | 00:30:11:11:11:12 | dynamic | |

Figure 4-17: Connection Status

4.4.6 SNMP

This page provides SNMP setting of the router as shown in [Figure 4-18](#).

SNMP

SNMP

Read Community

Write Community

☒ Enable ☐ Disable

System Identification

System Name

System Location

System Contact

Apply Settings

Cancel Changes

Figure 4-18: SNMP

| Object | Description |
|-----------------------------|---|
| Enable SNMP | Disable or enable the SNMP function. The default configuration is enabled. |
| Read/Write Community | Allows entering characters for SNMP Read/Write Community of the router. |
| System Name | Allows entering characters for system name of the router. |
| System Location | Allows entering characters for system location of the router. |
| System Contact | Allows entering characters for system contact of the router. |
| Apply Settings | Press this button to save and apply changes. |
| Cancel Changes | Press this button to undo any changes made locally and revert to previously saved values. |

4.5 Network

The Network function provides WAN, LAN and network configuration of the router as shown in [Figure 4-19](#).




Figure 4-19: Network Menu

| Object | Description |
|--------------------------|---------------------------------------|
| WAN Setup | Allows setting WAN interface. |
| WAN Advanced | Allows setting WAN Advanced settings. |
| LAN Setup | Allows setting LAN interface. |
| Routing | Allows setting Route. |
| IPv6 | Allows setting IPv6 WAN interface. |
| DHCP | Allows setting DHCP Server. |
| DDNS | Allows setting DDNS and PLANET DDNS. |
| MAC Address Clone | Allows setting WAN MAC Address Clone. |

4.5.1 WAN

This page is used to configure the parameters for Internet network which connects to the WAN port of the router as shown in [Figure 4-20](#). Here you may select the access method by clicking the item value of WAN access type.

WAN1

Connection Type

DHCP ▾

IP Address

Netmask

Gateway

DNS Server 1

DNS Server 2

WAN2

WAN

☐ Enable ☒ Disable

Connection Type

DHCP ▾

IP Address

Netmask

Gateway

DNS Server 1


DNS Server 2

Apply Settings
Cancel Changes

Figure 4-20: WAN

| Object | Description | |
|------------------------|---|---|
| WAN Access Type | Please select the corresponding WAN Access Type for the Internet, and fill the correct parameters from your local ISP in the fields which appear below. | |
| | Static | <p>Select Static IP Address if all the Internet ports' IP information is provided to you by your ISP (Internet Service Provider). You will need to enter the IP address, Netmask, Gateway, and DNS Server provided to you by your ISP.</p> <p>Each IP address entered in the fields must be in the appropriate IP form, which are four octets separated by a dot (x.x.x.x). The router will not accept the IP address if it is not in this format.</p> <p>IP Address</p> <p>Enter the IP address assigned by your ISP.</p> |

| Object | Description |
|-------------|---|
| | <p>Netmask Enter the Subnet Mask assigned by your ISP.</p> <p>Gateway Enter the Gateway assigned by your ISP.</p> <p>DNS Server The DNS server information will be supplied by your ISP.</p> |
| DHCP | Select DHCP Client to obtain IP Address information automatically from your ISP. |



WAN IP, whether obtained automatically or specified manually, should NOT be on the same IP net segment as the LAN IP; otherwise, the router will not work properly. In case of emergency, press the hardware-based "Reset" button.

4.5.2 WAN Advanced

This page is used to configure the advanced parameters for Internet area network which connects to the WAN port of your router as shown in [Figure 4-21](#). Here you may change the setting for Load Balance Weight, Detect Interval, Detect Link Up Threshold, etc...

WAN1

Load Balance Weight

3 ▾

External Connection Detection

☒ Enable ☐ Disable

Detect Interval

5

Seconds

Detect Link Up Threshold

8

Time(s)

Detect Link Down Threshold

3

Time(s)

Custom Detect Host 1

8.8.8.8

Custom Detect Host 2

208.67.222.222

WAN2

Load Balance Weight

2 ▾

External Connection Detection

☒ Enable ☐ Disable

Detect Interval

5

Seconds

Detect Link Up Threshold

8

Time(s)

Detect Link Down Threshold

3

Time(s)

Custom Detect Host 1

8.8.8.8

Custom Detect Host 2

208.67.222.222

Apply Settings

Cancel Changes

Figure 4-21: LAN Setup

| Object | Description |
|--------------------------------------|--|
| Load Balance Weight | Load Balance Weight allows you to set a relative weight (from 1 - 10) for each WAN port. |
| External Connection Detection | Enable to detect the status of WAN connection. |
| Detect Interval | Set the detect interval as you need. The recommended value is 5 (default). |
| Detect Link Up Threshold | Set the times for detecting link up. The recommended value is 8 (default). |
| Detect Link Down Threshold | Set the times for detecting link down. The recommended value is 3 (default). |
| Custom Detect Host | The host is used to check the internet connection is alive or not. |

4.5.3 LAN Setup

This page is used to configure the parameters for local area network which connects to the LAN port of your router as shown in [Figure 4-22](#). Here you may change the setting for IP address, subnet mask, DHCP, etc...

LAN Configuration

IP Address

192.168.1.1

Netmask

255.255.255.0

Apply Settings

Cancel Changes

Figure 4-22: LAN Setup

| Object | Description |
|-------------------|--|
| IP Address | The LAN IP address of the router and default is 192.168.1.1 . |
| Net Mask | Default is 255.255.255.0 . |

4.5.4 Routing

Please refer to the following sections for the details as shown in [Figure 4-23 and 24](#).

| Routing config list | | | | | | | |
|---------------------|------|-------------|---------|---------|-----------|---------|--------|
| Number | Type | Destination | Netmask | Gateway | Interface | Comment | Action |

| Current Routing table in the system | | | | |
|-------------------------------------|-------------|---------------|---------------|-----------|
| Number | Destination | Netmask | Gateway | Interface |
| 1 | 0.0.0.0 | 0.0.0.0 | 192.168.0.180 | LOCAL |
| 2 | 0.0.0.0 | 0.0.0.0 | 192.168.1.18 | WAN1 |
| 3 | 0.0.0.0 | 0.0.0.0 | 192.168.1.19 | WAN2 |
| 4 | 192.168.0.0 | 255.255.255.0 | 0.0.0.0 | LAN |
| 5 | 192.168.1.0 | 255.255.255.0 | 0.0.0.0 | WAN1 |
| 6 | 192.168.1.0 | 255.255.255.0 | 0.0.0.0 | WAN2 |

Add Route

Figure 4-23: Routing table

Add a routing rule

| | |
|-------------|-----------------------|
| Type | Host ▼ |
| Destination | <input type="text"/> |
| Netmask | 255.255.255.255 /32 ▼ |
| Gateway | <input type="text"/> |
| Interface | LAN ▼ |
| Comment | <input type="text"/> |

Apply Settings

Cancel Changes

Figure 4-24: Routing setup

Routing tables contain a list of IP addresses. Each IP address identifies a remote router (or other network gateway) that the local router is configured to recognize. For each IP address, the routing table additionally stores a network mask and other data that specifies the destination IP address ranges that remote device will accept.

| Object | Description |
|--------------------|---|
| Type | There are two types: Host and Net. When the Net type is selected, user does not need to input the Gateway. |
| Destination | The network or host IP address desired to access. |
| Net Mask | The subnet mask of destination IP. |

| Object | Description |
|------------------|--|
| Gateway | The gateway is the router or host's IP address to which packet was sent. It must be the same network segment with the WAN or LAN port. |
| Interface | Select the interface that the IP packet must use to transmit out of the router when this route is used. |
| Comment | Enter any words for recognition. |

4.5.5 WAN IPv6 Setting

This page is used to configure parameter for IPv6 internet network which connects to WAN port of the router as shown in [Figure 4-25](#). It allows you to enable IPv6 function and set up the parameters of the router's WAN. In this setting you may change WAN connection type and other settings.

WAN1 IPv6 Setting

Connection Type

IPv6 Address

Subnet Prefix Length

Default Gateway

WAN2 IPv6 Setting

Connection Type

IPv6 Address

Subnet Prefix Length

Default Gateway

Apply Settings
Cancel Changes

Figure 4-25: IPv6 WAN setup

| Object | Description |
|-----------------------------|--|
| Connection Type | Select IPv6 WAN type either by using DHCP or Static. |
| IPv6 Address | Enter the WAN IPv6 address. |
| Subnet Prefix Length | Enter the subnet prefix length. |
| Default Gateway | Enter the default gateway of the WAN port. |

4.5.6 DHCP

The DHCP service allows you to control the IP address configuration of all your network devices. When a client (host or other device such as networked printer, etc.) joins your network it will automatically get a valid IP address from a range of addresses and other settings from the DHCP service. The client must be configured to use DHCP, this is something called "automatic network configuration" and is often the default setting. The setup is shown in [Figure 4-26](#).

DHCP Server

DHCP Service

☒ Enable ☐ Disable

Start IP Address

192.168.1.

Maximum DHCP Users

Set DNS

☒ Automatically ☐ Manually

Primary DNS Server

Secondary DNS Server

WINS

Lease Time

minutes

Domain Name

Apply Settings

Cancel Changes

Figure 4-26: DHCP

| Object | Description |
|-------------------------------------|--|
| DHCP Service | By default, the DHCP Server is enabled, that the router will assign IP addresses to the DHCP clients automatically. If user needs to disable the function, please set it as disable. |
| Start IP Address | By default, the start IP address is 192.168.1.100. Please do not set it the same as the IP address of the router. |
| Maximum DHCP Users | By default, the Maximum DHCP Users is 101. It means the router will provide DHCP client with IP address from 192.168.1.100 to 192.168.1.200 when the start IP address is 192.168.1.100. |
| Set DNS | By default, it is set as Automatically, and the DNS server is the router's LAN IP address. If user needs to use specific DNS server, please set it as Manually, and then input a specific DNS server. |
| Primary/Secondary DNS Server | Input a specific DNS server. |
| WINS | Input a WINS server if needed. |
| Lease Time | Set the time for using one assigned IP. After the lease time, the DHCP client will need to get new IP addresses from the router. Default is 1440 minutes. |
| Domain Name | Input a domain name for the router. Default is Planet. |

4.5.7 DDNS

The router offers the DDNS (Dynamic Domain Name System) feature, which allows the hosting of a website, FTP server, or e-mail server with a fixed domain name (named by yourself) and a dynamic IP address, and then your friends can connect to your server by entering your domain name no matter what your IP address is. Before using this feature, you need to sign up for DDNS service providers such as **PLANET DDNS** (<http://www.planetddns.com>) and set up the domain name of your choice.

PLANET DDNS website provides a free DDNS (Dynamic Domain Name Server) service for PLANET devices. Whether the IP address used on your PLANET device supporting DDNS service is fixed or dynamic, you can easily connect the devices anywhere on the Internet with a meaningful or easy-remembered name you gave. PLANET DDNS provide two types of DDNS services. One is **PLANET DDNS** and the other is **PLANET Easy DDNS** as shown in [Figure 4-27](#).

PLANET DDNS

For example, you've just installed a PLANET IP camera with dynamic IP like 210.66.155.93 in the network. You can name this device as "Mycam1" and register a domain as Mycam1.planetddns.com at PLANET DDNS (<http://www.planetddns.com>). Thus, you don't need to memorize the exact IP address but just the URL link: Mycam1.planetddns.com.

PLANET Easy DDNS

PLANET Easy DDNS is an easy way to help user to get your Domain Name with just one click. You can just login to the Web Management Interface of your devices, say, your router, check the DDNS menu and just enable it. You don't need to go to <http://www.planetddns.com> to apply for a new account. Once you enabled the Easy DDNS, your PLANET Network Device will use the format PLxxxxxx where xxxxxx is the last 6 characters of your MAC address that can be found on the Web page or bottom label of the device. (For example, if the router's MAC address is A8-F7-E0-81-96-C9, it will be converted into pt8196c9.planetddns.com)

| Dynamic Domain Name Service | |
|-----------------------------|---|
| DDNS Service | <input checked="" type="radio"/> Enable <input type="radio"/> Disable |
| Interface | WAN1 ▼ |
| DDNS Type | PLANET DDNS ▼ |
| Easy DDNS | Disable ▼ |
| User Name | <input type="text"/> |
| Password | <input type="text"/> |
| Host Name | <input type="text"/> |
| Interval | 120 |
| Update Status | unknow status |

Figure 4-27: PLANET DDNS

| Object | Description |
|----------------------|---|
| DDNS Service | By default, the DDNS service is disabled. If user needs to enable the function, please set it as enable. |
| Interface | User is able to select the interface for DDNS service using. By default, the interface is WAN 1. |
| DDNS Type | There are three options: <ol style="list-style-type: none"> 1. PLANET DDNS: Activate PLANET DDNS service. 2. DynDNS: Activate DynDNS service. 3. NOIP: Activate NOIP service. <p>Note that please first register with the DDNS service and set up the domain name of your choice to begin using it.</p> |
| Easy DDNS | When the PLANET DDNS service is activated, user is able to select to enable or disable Easy DDNS. When this function is enabled, DDNS hostname will appear automatically. User doesn't go to http://www.planetddns.com to apply for a new account. |
| User Name | The user name is used to log into DDNS service. |
| Password | The password is used to log into DDNS service. |
| Host Name | The host name as registered with your DDNS provider. |
| Interval | Set the update interval of the DDNS function. |
| Update Status | Show the connection status of the DDNS function. |

4.5.8 MAC Address Clone

Clone or change the MAC address of the WAN interface. The setup is shown in [Figure 4-28](#).

MAC Address Clone - WAN1

Clone WAN MAC

☐ Enable
 ☒ Disable

MAC Address

MAC Address Clone - WAN2

Clone WAN MAC

☐ Enable
 ☒ Disable

MAC Address

Apply Settings

Cancel Changes

Figure 4-28: MAC Address Clone

| Object | Description |
|----------------------|---|
| Clone WAN MAC | Set the function as enable or disable. |
| MAC Address | Input a MAC Address, such as A8:F7:E0:00:06:62. |

4.6 Security

The Security menu provides Firewall, Access Filtering and other functions as shown in [Figure 4-29](#). Please refer to the following sections for the details.




Figure 4-29: Security menu

| Object | Description |
|------------------------------|--|
| Firewall | Allows setting DoS (Denial of Service) protection as enable. |
| MAC Filtering | Allows setting MAC Filtering. |
| IP Filtering | Allows setting IP Filtering. |
| Web Filtering | Allow setting Web Filtering. |
| Port Range Forwarding | Allow setting Port Forwarding. |
| DMZ | Allow setting DMZ. |

4.6.1 Firewall

A "Denial-of-Service" (DoS) attack is characterized by an explicit attempt by hackers to prevent legitimate users of a service from using that service. The router can prevent specific DoS attacks as shown in [Figure 4-30](#).

Firewall Protection

SPI Firewall

☒ Enable
 ☐ Disable

DDos

| | | | |
|------------------|---|----|----------------|
| Block SYN Flood | <input checked="" type="radio"/> Enable <input type="radio"/> Disable | 30 | Packets/Second |
| Block FIN Flood | <input type="radio"/> Enable <input checked="" type="radio"/> Disable | 30 | Packets/Second |
| Block UDP Flood | <input type="radio"/> Enable <input checked="" type="radio"/> Disable | 30 | Packets/Second |
| Block ICMP Flood | <input type="radio"/> Enable <input checked="" type="radio"/> Disable | 5 | Packets/Second |
| IP TearDrop | <input type="radio"/> Enable <input checked="" type="radio"/> Disable | | |
| PingOfDeath | <input type="radio"/> Enable <input checked="" type="radio"/> Disable | | |

System Security

| | | | |
|-------------------|---|--|--|
| Block WAN Ping | <input type="radio"/> Enable <input checked="" type="radio"/> Disable | | |
| Remote Management | <input type="radio"/> Enable <input checked="" type="radio"/> Disable | | |

Apply Settings

Cancel Changes

Figure 4-30: Firewall

| Object | Description |
|------------------------|---|
| SPI Firewall | <p>The SPI Firewall prevents attack and improper access to network resources.</p> <p>The default configuration is enabled.</p> |
| Block SYN Flood | <p>SYN Flood is a popular attack way. DoS and DDoS are TCP protocols. Hackers like using this method to make a counterfeit of connection, and the CPU and memory, and so on.</p> <p>The default configuration is enabled.</p> |
| Block FIN Flood | <p>If the function is enabled, when the number of the current FIN packets is beyond the set value, the router will start the blocking function immediately.</p> <p>The default configuration is disabled.</p> |

| | |
|--------------------------|---|
| Block UDP Flood | <p>If the function is enabled, when the number of the current UPD-FLOOD packets is beyond the set value, the router will start the blocking function immediately.</p> <p>The default configuration is disabled.</p> |
| Block ICMP Flood | <p>ICMP is kind of a pack of TCP/IP; its important function is to transfer simple signal on the Internet. There are two normal attack ways which hackers like to use, Ping of Death and Smurf attack.</p> <p>The default configuration is disabled.</p> |
| IP TearDrop | <p>If the function is enabled, the router will block Teardrop attack that targeting on TCP/IP fragmentation reassembly codes.</p> |
| Ping Of Death | <p>If the function is enabled, the router will block Ping of Death attack that aims to disrupt a targeted machine by sending a packet larger than maximum allowable size causing the target machine to freeze or crash.</p> |
| Block WAN Ping | <p>Enable the function to allow the Ping access from the Internet network.</p> <p>The default configuration is disabled.</p> |
| Remote Management | <p>Enable the function to allow the web server access of the router from the Internet network.</p> <p>The default configuration is disabled.</p> |

4.6.2 MAC Filtering

Entries in this table are used to restrict certain types of data packets from your local network or Internet through the router. Use of such filters can be helpful in securing or restricting your local network as shown in [Figure 4-31](#).




Figure 4-31: MAC Filtering

| Object | Description |
|-----------------------------|---|
| Enable MAC Filtering | Set the function as enable or disable. When the function is enabled, the router will block traffic of the MAC address on the list. |
| Interface | Select the function works on LAN, WAN or both. If you want to block a LAN device's MAC address, please select LAN, vice versa. |
| MAC Address | Input a MAC address you want to control, such as A8:F7:E0:00:06:62. |
| Add | When you input a MAC address, please click the "Add" button to add it into the list. |
| Remove | If you want to remove a MAC address from the list, please click on the MAC address, and then click the "Remove" button to remove it. |
| Remove All | If you want to remove all MAC addresses from the list, please click the "Remove All" button to remove all. |

4.6.3 IP Filtering

IP Filtering is used to deny LAN users from accessing the public IP address on internet as shown in [Figure 4-32](#). To begin blocking access to an IP address, enable IP Filtering and enter the IP address of the web site you wish to block.




Figure 4-32: IP Filtering

| Object | Description |
|------------------------------|--|
| IP Filtering | Set the function as enable or disable. |
| Add IP Filtering Rule | Go to the Add Filtering Rule page to add a new rule. |




Figure 4-33: IP Filter Rule Setting

| Object | Description |
|--|--|
| Enable | Set the rule as enable or disable. |
| Source IP Address | Input the IP address of LAN user (such as PC or laptop) which you want to control. |
| Anywhere (of source IP Address) | Check the box if you want to control all LAN users. |

| Object | Description |
|---|--|
| Destination IP Address | Input the IP address of web site which you want to block. |
| Anywhere (of destination IP Address) | Check the box if you want to control all web sites, it means the LAN user can't visit any web site. |
| Destination Port | Input the port of destination IP Address which you want to block. Leave it as blank if you want to block all ports of the web site. |
| Protocol | Select the protocol type (TCP, UDP or all). If you are unsure, please leave it to the default all protocol. |

4.6.4 Web Filtering

Web filtering is used to deny LAN users from accessing the internet as shown in [Figure 4-34](#). Block those URLs which contain keywords listed below.

Web Filtering

Web Filtering
☐ Enable
☒ Disable

Web Filtering Rules

| No. | Rule Enable | Filter Keyword | Filter Type | Action |
|-----------------------------------|-------------|----------------|-------------|--------|
| <div>Add Web Filtering Rule</div> | | | | |

Figure 4-34: Web Filtering

| Object | Description |
|-------------------------------|--|
| Web Filtering | Set the function as enable or disable. |
| Add Web Filtering Rule | Go to the Add Web Filtering Rule page to add a new rule. |

Web Filter Settings

Status

Filter Keyword

Apply Settings

Cancel Changes

Figure 4-35: Web Filtering Rule Setting

| Object | Description |
|--------|-------------|
|--------|-------------|

| Object | Description |
|----------------|---|
| Status | Set the rule as enable or disable. |
| Filter Keyword | Input the URL address that you want to filter, such as www.yahoo.com. |

4.6.5 Port Forwarding

Entries in this table allow you to automatically redirect common network services to a specific machine behind the NAT firewall as shown in [Figure 4-36](#). These settings are only necessary if you wish to host some sort of server like a web server or mail server on the private local network behind your Router's NAT firewall.

Port Forwarding

Port Forwarding
☐ Enable
☒ Disable

Port Forwarding Rules

| No. | Rule Name | External Interface | Protocol | External Port Range | Internal IP | Internal Port Range | Delete |
|-----|-----------|--------------------|----------|---------------------|-------------|---------------------|--------|
|-----|-----------|--------------------|----------|---------------------|-------------|---------------------|--------|

Add Port Forwarding Rule

Figure 4-36: Port Forwarding

| Object | Description |
|--------------------------|--|
| Port Forwarding | Set the function as enable or disable. |
| Add Port Forwarding Rule | Go to the Add Port Forwarding Rule page to add a new rule. |

Port Forwarding

Rule Name

Protocol
Both ▼

External Service Port
 ~

Virtual Server IP Address

Internal Service Port
 ~

Apply Settings
Cancel Changes

Figure 4-37: Port Forwarding Rule Setting

| Object | Description |
|--------|-------------|
|--------|-------------|

| Object | Description |
|----------------------------------|---|
| Rule Name | Enter any words for recognition. |
| Protocol | Select the protocol type (TCP, UDP or both). If you are unsure, please leave it to the default both protocols. |
| External Service Port | Enter the external ports you want to control. For TCP and UDP services, enter the beginning of the range of port numbers used by the service. If the service uses a single port number, enter it in both the start and finish fields. |
| Virtual Server IP Address | Enter the local IP address. |
| Internal Service Port | Enter local ports you want to control. For TCP and UDP Services, enter the beginning of the range of port numbers used by the service. If the service uses a single port number, enter it in both the start and finish fields. |

4.6.6 DMZ

A Demilitarized Zone is used to provide Internet services without sacrificing unauthorized access to its local private network as shown in [Figure 4-38](#). Typically, the DMZ host contains devices accessible to Internet traffic, such as Web (HTTP) servers, FTP servers, SMTP (e-mail) servers and DNS servers.

DMZ - WAN1

DMZ ☐ Enable ☒ Disable
DMZ IP Address

DMZ - WAN2

DMZ ☐ Enable ☒ Disable
DMZ IP Address

Figure 4-38: DMZ

| Object | Description |
|------------|--|
| DMZ | Set the function as enable or disable. If the DMZ function is enabled, it means that you set up DMZ at a particular computer to be exposed to the Internet so that some applications/software, especially Internet/online game can have two way connections. |

| Object | Description |
|-----------------------|--|
| DMZ IP Address | Enter the IP address of a particular host in your LAN which will receive all the packets originally going to the WAN port/Public IP address above. |

4.7 VPN

To obtain a private and secure network link, the router is capable of establishing VPN connections. When used in combination with remote client authentication, it links the business' remote sites and users, conveniently providing the enterprise with an encrypted network communication method. By allowing the enterprise to utilize the Internet as a means of transferring data across the network, it forms one of the most effective and secures options for enterprises to adopt in comparison to other methods.

The Maintenance menu provides the following features for managing the system as [Figure 4-39](#) is shown below:



Figure 4-39: VPN Menu

| Object | Description |
|-----------------------|---------------------------------------|
| IPsec | Allows setting IPsec function. |
| GRE | Allows setting GRE function. |
| PPTP | Allows setting PPTP function. |
| L2TP | Allow setting L2TP function. |
| SSL VPN | Allow setting SSL VPN function. |
| VPN Connection | Allow checking VPN Connection Status. |

4.6.7 IPsec

IPSec (IP Security) is a generic standardized VPN solution. IPSec must be implemented in the IP stack which is part of the kernel. Since IPSec is a standardized protocol it is compatible to most vendors that implement IPSec. It allows users to have an encrypted network session by standard **IKE** (Internet Key Exchange). We strongly encourage you to use IPSec only if you need to because of interoperability purposes. When IPSec lifetime is specified, the device can randomly refresh and identify forged IKE's during the IPSec lifetime.

This page will allow you to modify the user name and passwords as shown in [Figure 4-40](#).

IPSec Tunnel Lists

| No. | Name | Interface | Status | Action |
|-----|------|-----------|--------|--------|
| | | | | |

Add IPSec Tunnel

Figure 4-40: IPSec

| Object | Description |
|------------------|--|
| Add IPSec Tunnel | Go to the Add IPSec Tunnel page to add a new tunnel. |

IPSec Tunnel

IPSec Tunnel Enable ☒

Tunnel Name

Interface ☒ WAN1 ☐ WAN2

Local Network

Local Netmask

Remote IP Address

Remote Network

Remote Netmask

Detection

Dead Peer Detection ☒

Time Interval Seconds Timeout Seconds Action

Authentication

Preshare Key

IKE Setting

Phase 1

IKE ☒ v1 ☐ v2

Connection Type ☒ Main ☐ Aggressive

ISAKMP DH Group

IKE SA Lifetime hours

Phase 2

ESP

ESP Keylife hours

Perfect Forward Secrecy (PFS) ☐ Yes ☒ No

Figure 4-41: IPSec Tunnel

| Object | Description |
|----------------------------|--|
| IPSec Tunnel Enable | Check the box to enable the function. |
| Tunnel Name | Enter any words for recognition. |
| Interface | This is only available for host-to-host connections and specifies to which interface the host is connecting. 1. WAN 1. 2. WAN 2. |
| Local Network | The local subnet in CIDR notation. For instance, "192.168.1.0". |
| Local Netmask | The netmask of this router. |

| | |
|----------------------------|--|
| Remote IP Address | Input the IP address of the remote host. For instance, "210.66.1.10". |
| Remote Network | The remote subnet in CIDR notation. For instance, "210.66.1.0". |
| Remote Netmask | The netmask of the remote host. |
| Dead Peer Detection | <p>Set up the detection time of DPD (Dead Peer Detection).</p> <p>By default, the DPD detection's gap is 30 seconds, over 150 seconds to think that is the broken line.</p> <p>When VPN detects opposite party reaction time, the function will take one of the actions: "Hold" stand for the system will retain IPSec SA, "Clear" stand for the tunnel will clean away and waits for the new sessions, "Restart" will delete the IPSec SA and reset VPN tunnel.</p> |
| Preshare Key | Enter a pass phrase to be used to authenticate the other side of the tunnel. Should be the same with the remote host. |
| IKE | Select the IKE (Internet Key Exchange) version. |
| Connection Type | <ol style="list-style-type: none"> 1. Main. 2. Aggressive. |
| ISAKMP | <p>It provides the way to create the SA between two PCs. The SA can access the encoding between two PCs, and the IT administrator can assign of which key size or Preshare Key and algorithm to use. The SA comes in many connection ways.</p> <ol style="list-style-type: none"> 1. AES: All using a 128-bit, 192-bit and 256-bit key. AES is a commonly seen and adopted nowadays. 2. 3DES: Triple DES is a block cipher formed from the DES cipher by using it three times. It can achieve an algorithm up to 168 bits. 3. SHA1: The SHA1 is a revision of SHA. It has improved the shortcomings of SHA. By producing summary hash values, it can achieve an algorithm up to 160 bits. 4. SHA2: It can be choice 256, 384 or 512. 5. MD5 Algorithm: MD5 processes a variable-length message into a fixed-length output of 128 bits. 6. DH Group: It can be choice 1, 2, 5, 14, 15, 16, 17, or 18. |
| IKE SA Lifetime | You can specify how long IKE packets are valid. |
| ESP | <p>It offers AES, 3 DES, SHA 1, SHA2, and MD5.</p> <ol style="list-style-type: none"> 1. AES: All using a 128-bit, 192-bit and 256-bit key. AES is a commonly seen and adopted nowadays. 2. 3DES: Triple DES is a block cipher formed from the DES cipher |

| | |
|--------------------------------------|---|
| | <p>by using it three times. It can achieve an algorithm up to 168 bits.</p> <p>3. SHA1: The SHA1 is a revision of SHA. It has improved the shortcomings of SHA. By producing summary hash values, it can achieve an algorithm up to 160 bits.</p> <p>4. SHA2: It can be choice 256, 384 or 512.</p> <p>5. MD5 Algorithm: MD5 processes a variable-length message into a fixed-length output of 128 bits.</p> |
| ESP Keylife | You can specify how long ESP packets are valid. |
| Perfect Forward Secrecy (PFS) | Set the function as enable or disable. |

4.6.8 GRE

This section assists you in setting the GRE Tunnel as shown in [Figure 4-42](#).

GRE Tunnel

GRE Tunnel
☐ Enable
☒ Disable

GRE Tunnel Lists

| No. | Name | Enable | Through | Peer WAN IP Addr | Peer Subnet | Peer Tunnel IP | Local Tunnel IP | Local Netmask | Action |
|---------------------------|------|--------|---------|------------------|-------------|----------------|-----------------|---------------|--------|
| <div>Add GRE Tunnel</div> | | | | | | | | | |

Figure 4-42: GRE

| Object | Description |
|-----------------------|--|
| GRE Tunnel | Set the function as enable or disable. |
| Add GRE Tunnel | Go to the Add GRE Tunnel page to add a new tunnel. |

GRE Tunnel

| | |
|-------------------------|--|
| Status | Disable ▼ |
| Name | <input type="text" value="Tunnel name"/> |
| Through | LAN ▼ |
| Peer Wan IP Address | <input type="text" value="Remote IP Address"/> |
| Peer Subnet Mask | <input type="text" value="10.10.10.0/24"/> |
| Peer Tunnel IP Address | <input type="text" value="10.10.10.2"/> |
| Local Tunnel IP Address | <input type="text" value="10.10.10.1"/> |
| Local Subnet Mask | <input type="text" value="255.255.255.255 /32 ▼"/> |

Apply Settings
Cancel Changes

Figure 4-43: GRE Tunnel

| Object | Description |
|--------------------------------|---|
| Active | Check the box to enable the function. |
| Tunnel Name | Enter any words for recognition. |
| Through | <p>This is only available for host-to-host connections and specifies to which interface the host is connecting.</p> <ol style="list-style-type: none"> 1. LAN. 2. WAN 1. 3. WAN 2. |
| Peer WAN IP Address | Input the IP address of the remote host. For instance, "210.66.1.10". |
| Peer Netmask | The remote subnet in CIDR notation. For instance, "210.66.1.0/24". |
| Peer Tunnel IP Address | Input the Tunnel IP address of remote host. |
| Local Tunnel IP Address | Input the Tunnel IP address of remote host. |
| Local Netmask | Input the Tunnel IP address of the router. |

4.6.9 PPTP Server

Use the IP address and the scope option needs to match the far-end the PPTP server; its goal is to use the PPTP channel technology, and establish Site to Site VPN where the channel can have equally good results from different methods with IPSec. The PPTP server is shown in [Figure 4-44](#).

PPTP Server

PPTP Server

☐ Enable ☒ Disable

Broadcast

☐ Enable ☒ Disable

Force MPPE Encryption

☒ Enable ☐ Disable

CHAP

☒ Enable ☐ Disable

MSCHAP

☒ Enable ☐ Disable

MSCHAP v2

☒ Enable ☐ Disable

DNS1

DNS2

WINS1

WINS2

Server IP Address

Clients IP Address Start

Clients IP Address End

| | User | Password |
|---|-----------------------------------|-----------------------------------|
| 1 | <input type="text" value="test"/> | <input type="text" value="test"/> |
| 2 | <input type="text" value="user"/> | <input type="text" value="1234"/> |
| 3 | <input type="text" value="user"/> | <input type="text" value="1234"/> |
| 4 | <input type="text" value="user"/> | <input type="text" value="1234"/> |
| 5 | <input type="text" value="user"/> | <input type="text" value="1234"/> |

Apply Settings

Cancel Changes

Figure 4-44: PPTP server

| Object | Description |
|------------------------------|--|
| PPTP Server | Set the function as enable or disable. |
| Broadcast | Enter any words for recognition. |
| Force MPPE Encryption | Set the encryption as enable or disable. |
| CHAP | Set the authentication as enable or disable. |
| MSCHAP | Set the authentication as enable or disable. |

| | |
|---------------------------------------|--|
| MSCHAP v2 | Set the authentication as enable or disable. |
| DNS | When the PPTP client connects to the PPTP server, it will assign the DNS server IP address to client. |
| WINS | When the PPTP client connects to the PPTP server, it will assign the WINS server IP address to client. |
| Server IP Address | Input the IP address of the PPTP Server. For instance, "192.168.10.1". |
| Clients IP Address (Start/End) | When the VPN connection is established, the VPN client will get IP address from the VPN Server, please set the range of IP Address. For instance, the start IP address is "192.168.10.10", the end IP address is "192.168.10.100". |
| User and Password | Create the username and password for the VPN client. |

4.6.10 L2TP Server

This section assists you in setting the L2TP Server as shown in [Figure 4-45](#).

L2TP Server

L2TP Server

Server IP Address

Clients IP Address Start

Clients IP Address End

With IPsec

Preshare Key

☐ Enable ☒ Disable

☐ Enable ☒ Disable

Users

| | User | Password |
|---|-----------------------------------|-----------------------------------|
| 1 | <input type="text" value="test"/> | <input type="text" value="test"/> |
| 2 | <input type="text" value="user"/> | <input type="text" value="1234"/> |
| 3 | <input type="text" value="user"/> | <input type="text" value="1234"/> |
| 4 | <input type="text" value="user"/> | <input type="text" value="1234"/> |
| 5 | <input type="text" value="user"/> | <input type="text" value="1234"/> |

IPsec

Phase 1

Connection Type ☒ Main ☐ Aggressive

ISAKMP

IKE SA Lifetime hours

Phase 2

ESP

ESP Keylife hours

Apply Settings

Cancel Changes

Figure 4-45: L2TP Server

| Object | Description |
|---------------------------------------|---|
| L2TP Server | Set the function as enable or disable. |
| Server IP Address | Input the IP address of the L2TP Server. For instance, "192.168.50.1". |
| Clients IP Address (Start/End) | When the VPN connection is established, the VPN client will get IP address from the VPN Server, please set the range of IP Address. For instance, the start IP address is "192.168.50.100", the end IP address is "192.168.50.200". |

| Object | Description |
|--------------------------|--|
| With IPsec | Set the function as enable to make the L2TP work with IPsec encryption. |
| Preshare Key | Enter a pass phrase. |
| User and Password | Create the username and password for the VPN client. |
| Connection Type | <ol style="list-style-type: none"> 1. Main. 2. Aggressive. |
| ISAKMP | <p>It provides the way to create the SA between two PCs. The SA can access the encoding between two PCs, and the IT administrator can assign of which key size or Preshare Key and algorithm to use. The SA comes in many connection ways.</p> <ol style="list-style-type: none"> 1. AES: All using a 128-bit, 192-bit and 256-bit key. AES is a commonly seen and adopted nowadays. 2. 3DES: Triple DES is a block cipher formed from the DES cipher by using it three times. It can achieve an algorithm up to 168 bits. 3. SHA1: The SHA1 is a revision of SHA. It has improved the shortcomings of SHA. By producing summary hash values, it can achieve an algorithm up to 160 bits. 4. SHA2: It can be choice 256, 384 or 512. 5. MD5 Algorithm: MD5 processes a variable-length message into a fixed-length output of 128 bits. 6. DH Group: It can be choice 1, 2, 5, 14, 15, 16, 17, or 18. |
| IKE SA Lifetime | You can specify how long IKE packets are valid. |
| ESP | <p>It offers AES, 3 DES, SHA 1, SHA2, and MD5.</p> <ol style="list-style-type: none"> 1. AES: All using a 128-bit, 192-bit and 256-bit key. AES is a commonly seen and adopted nowadays. 2. 3DES: Triple DES is a block cipher formed from the DES cipher by using it three times. It can achieve an algorithm up to 168 bits. 3. SHA1: The SHA1 is a revision of SHA. It has improved the shortcomings of SHA. By producing summary hash values, it can achieve an algorithm up to 160 bits. 4. SHA2: It can be choice 256, 384 or 512. 5. MD5 Algorithm: MD5 processes a variable-length message into a fixed-length output of 128 bits. |
| ESP Keylife | You can specify how long ESP packets are valid. |

4.6.11 SSL VPN

This section assists you in setting the SSL Server as shown in [Figure 4-46](#).

SSL Server

| | | |
|------------------------|---|-------------|
| SSL VPN Server | <input type="radio"/> Enable <input checked="" type="radio"/> Disable | |
| Port | <input type="text" value="1194"/> | |
| Tunnel Protocol | <input type="text" value="UDP"/> | |
| Virtual Network Device | <input type="text" value="TUN"/> | |
| Interface | <input type="text" value="LAN"/> | 192.168.1.1 |
| VPN Network | <input type="text" value="192.168.20.0"/> | |
| Network Mask | <input type="text" value="255.255.255.0"/> | |
| Encryption Cipher | <input type="text" value="AES-128 CBC"/> | |
| Hash Algorithm | <input type="text" value="SHA1"/> | |
| Export client.ovpn | <input type="button" value="Export"/> | |

Figure 4-46: SSL Server

| Object | Description |
|-------------------------------|---|
| SSL VPN Server | Set the function as enable or disable. |
| Port | Set a port for the SSL Service. Default port is 1194. |
| Tunnel Protocol | Set the protocol as TCP or UDP. |
| Virtual Network Device | Set the Virtual Network Device as TUN or TAP. |
| Interface | User is able to select the interface for SSL service using. |
| VPN Network | The VPN subnet in CIDR notation. For instance, "192.168.20.0". |
| Network Mask | The netmask of the VPN. |
| Encryption Cipher | There are four encryption types: None, AES-128 CBC, AES-192 CBC or AES-256 CBC. |
| Hash Algorithm | There are five types of Hash Algorithm: None, SHA1, SHA1, SHA512 or MD5. |
| Export client.ovpn | Export a configuration for the SSL client. User is able to upload it to VPN client (such as Open VPN software). |

4.6.12 VPN Connection

This page shows the VPN connection status as shown in [Figure 4-47](#).

| VPN Connection Status | | | | | | |
|---|----------------|----------|-----------|--------------|---------------|--|
| <div> <div>IPsec</div> <div>GRE</div> <div>PPTP</div> <div>L2TP</div> <div>SSL VPN</div> </div> | | | | | | |
| Type | Connected Time | Local IP | Remote IP | Local Subnet | Remote Subnet | |

Figure 4-47: VPN Connection Status

| Object | Description |
|------------------------------|--|
| VPN Connection Status | Click the IPsec/GRE/.../SSL VPN bookmark to check the current connection status. |

4.7 Maintenance

The Maintenance menu provides the following features for managing the system as [Figure 4-48](#) is shown below:




Figure 4-48: Maintenance Menu

| Object | Description |
|-----------------------------------|---|
| Administrator | Allows changing the login username and password. |
| Date & Time | Allows setting Date & Time function. |
| Save/Restore Configuration | Export the router's configuration to local or USB sticker. Restore the router's configuration from local or USB sticker. |
| Firmware Upgrade | Upgrade the firmware from local or USB storage. |
| Reboot / Reset | Reboot or reset the system. |
| Auto Reboot | Allows setting auto-reboot schedule. |
| Diagnostics | Allows you to issue ICMP PING packets to troubleshoot IP. |

4.7.1 Administrator

To ensure the router's security is secure, you will be asked for your password when you access the router's Web-based utility. The default user name and password are "admin". This page will allow you to modify the user name and passwords as shown in [Figure 4-21](#).

Account Password

| | |
|------------------|------------------------------------|
| Username | <input type="text" value="admin"/> |
| Password | <input type="password"/> |
| Confirm Password | <input type="password"/> |

Apply Settings
Cancel Changes

Figure 4-48: Administrator

| Object | Description |
|------------------|-----------------------|
| Username | Input a new username. |
| Password | Input a new password. |
| Confirm Password | Input password again. |

4.7.2 Date and Time

This section assists you in setting the system time of the router. You are able to either select to set the time and date manually or automatically obtain the GMT time from Internet as shown in [Figure 4-49](#).

Date and Time

| | |
|-------------------|--|
| Current Time | Year <input type="text" value="2019"/> Month <input type="text" value="10"/> Day <input type="text" value="22"/> Hour <input type="text" value="10"/> Minute <input type="text" value="27"/> Second <input type="text" value="12"/> <input type="button" value="Copy Computer Time"/> |
| Time Zone Select | <input type="text" value="(GMT+08:00)Taipei"/> ▼ |
| NTP Client Update | <input type="radio"/> Enable <input checked="" type="radio"/> Disable |
| NTP Server | <input type="text" value="time.nist.gov"/> <input type="text" value="time.windows.com"/> <input type="text" value="time.stdtime.gov.tw"/> <input type="text"/> |

Apply Settings
Cancel Changes

Figure 4-49: Date and Time

| Object | Description |
|------------------|---|
| Current Time | Show the current time. User is able to set time and date manually. |
| Time Zone Select | Select the time zone of the country you are currently in. The router will |

| | |
|--------------------------|---|
| | set its time based on your selection. |
| NTP Client Update | Once this function is enabled, router will automatically update current time from NTP server. |
| NTP Server | User may use the default NTP sever or input NTP server manually. |

4.7.3 Save/Restore Configuration

This page shows the status of the configuration. You may save the setting file to either USB storage or PC and load the setting file from USB storage or PC as Figure 4-50 is shown below:






Figure 4-50: Save/Restore Configuration

■ Save Setting to PC

| Object | Description |
|-----------------------------|--|
| Configuration Export | Press the  button to save setting file to PC. |
| Configuration Import | Press the  button to select the setting file, and then press the  button to upload setting file from PC. |


■ Save Setting to USB Storage

| Object | Description |
|--------|-------------|
|--------|-------------|

| Object | Description |
|---------------------------------------|---|
| USB storage | The status of USB storage. |
| Backup Settings to USB Storage | Press the  button to save setting file to USB storage. |
| Load Settings from USB Storage | Press the  button to upload setting file from USB storage. |
| Unmount | Before removing the USB storage from the router, please press the  button first. |

4.7.4 Upgrading Firmware

This page provides the firmware upgrade of the router as shown in [Figure 4-51](#).



The screenshot shows a web interface titled "Firmware Upgrade". It contains a "Select File" label, a "Choose File" button, and the text "No file chosen". Below these is an "Upgrade" button.

Figure 4-51: Firmware upgrade

| Object | Description |
|--------------------|---|
| Choose File | Press the button to select the firmware. |
| Upgrade | Press the button to upgrade firmware to system. |

4.7.5 Reboot / Reset

This page enables the device to be rebooted from a remote location. Once the Reboot button is pressed, users have to re-log in the Web interface as [Figure 4-52](#) is shown below:

Reboot / Reset

Reboot Button

Reset Button

☐ I'd like to keep the network profiles.
Keep your current network profiles and reset all other configuration to factory defaults.

Figure 4-52: Reboot/Reset

| Object | Description |
|---|---|
| Reboot | Press the button to reboot system. |
| Reset | Press the button to restore all settings to factory default settings. |
| I'd like to keep the network profiles. | Check the box and then press the <input type="button" value="Reset to Default"/> button to keep the current network profiles and reset all other configuration to factory defaults. |

4.7.6 Diagnostics

The page allows you to issue ICMP PING packets to troubleshoot IP connectivity issues. After you press "Ping", ICMP packets are transmitted, and the sequence number and roundtrip time are displayed upon reception of a reply. The Page refreshes automatically until responses to all packets are received, or until a timeout occurs. The ICMP Ping is shown in [Figure 4-53](#).

Ping Test

Interface
Target Host
Numbers of Packets
Ping

Figure 4-53: Ping

| Object | Description |
|---------------------------|---|
| Interface | Select an interface of the router. |
| Target Host | The destination IP Address or domain. |
| Numbers of Packets | Set the numbers of packets will be transmitted, the maximum is 100. |
| Ping | The time of ping. |



Be sure the target IP address is within the same network subnet of the router, or you have to set up the correct gateway IP address.


Appendix A: DDNS Application

Configuring PLANET DDNS steps:

Step 1: Visit DDNS provider's web site and register an account if you do not have one yet. For example, register an account at <http://planetddns.com>

Step 2: Enable DDNS option through accessing web page of the device.

Step 3: Input all DDNS settings.



The screenshot shows the PLANET DDNS website. The header features the PLANET logo and navigation links for 'PLANET Website', 'FAQ', and 'Support'. The main content area includes a 'Sign in' form with fields for 'ID / Email' and a password, a 'Sign in' button, and links for 'Forgotten Password' and 'Create A New Account'. Below the sign-in form, there are three product showcases: 'XRT-401F Internet Broadband Router', 'ICA-HM132 2 Mega-Pixel 20M IR Vari-Focal Dome IP Camera', and 'ICA-HM316 2 Mega-Pixel 11n Outdoor IR IP Camera', each with a 'More Info' button. At the bottom, there is a section titled 'Access anytime & anywhere' with a description of the service, a 'Support & Download' section with a 'Go!' button, and a footer with 'About DDNS | Term of Usage' and 'PLANET Technology Corp. Copyright ©2012 All Rights Reserved.'