


Smart Radiator Thermostat Compatibility Guide

Radiator valves Non-thermostatic radiator valves

A non-thermostatic or manualvalve is a simple on/off valve that works like a tap. It regulates hot water fow to the radiator and changes the room's temperature only when it is manually turned on or off.

The illustrations on the right show an example of common non-thermostatic radiator.




Manual thermostatic radiator valves & Intelligent thermostatic radiator valves

A thermostatic radiator valve senses the room temperature and automatically adjusts the hot water flow to the radiator tomaintain a constant temperature in the room.

The T55 smart radiator thermostat only works with thermostatic radiator valves and it replaces your existing thermostatic valve head.

Please check the list on the next page to find out if your thermostatic radiator valve is compatible with T55, if you need an adapter to install T55 please check if we provide this adapter or not.



Brand name	Type of connection	Is T55compatible?			n adapter ovided?	Picture
Di di lu fidifie	(Thread/ Clamp)	Yes/No	Connection	Yes/No	Adapter name	Picture
altecnic	Thread: M30 x 1.5 mm	\bigcirc	No adapter needed	\bigotimes	\bigotimes	
Braukmann	Thread: M40 x 1.5 mm	X	No adapter available	×	X	
brv	Thread: M30 x 1.5 mm	×	No adapter available	X	X	
BOSS THERM™	Thread: M28 x 1.5 mm	X	With adapter	X	\bigotimes	
Caleff	Clamp: 23 mm		With adapter		Caleffi:Clip type Diameter 23mm1/2 valve	
Caleff	Thread: M30 x 1.5 mm		No adapter needed	X	X	
Carlo Poletti	Thread: M30 x 1.5 mm		No adapter needed	X	X	
COMAP	Thread: M30 x 1.5 mm		No adapter needed	X	X	

Brand name	Type of connection	Is T55co	ompatible?	Is an adapter provided?		Picture
Brana name	(Thread/ Clamp)	Yes/No	Connection	Yes/No	Adapter name	riotaro
COMAP	Thread: M28 x 1.5 mm	\bigotimes	With adapter	\bigotimes	\bigotimes	
Danfoss	Thread: M30 x 1.5 mm		No adapter needed	\bigotimes	X	
Danfoss/Honeywell	Clamp: 23mm with notches		With adapter		Danfoss:Clip type Diameter 23mm with notches 1/2 valve (RA)	
Danfoss Danfoss	Clamp: 34 mm with 4 notches		With adapter	X	Danfoss:Clip type Diameter 34mm-4 notches 3/4 valve + long plunger (RAV)	
Danfoss Danfoss	Clamp: 25.5 mm with 4 notches	X	With adapter	×	\bigotimes	
Danfoss Danfoss	Clamp: 32 mm with 2 notches	X	RTL-valve	X	X	
Danfoss Danfoss	Thread: M30 x 1.5 mm	\otimes	With adapter	X	X	
Drayton	Thread: M30 x 1.5 mm		No adapter needed	X	X	

Brand name	Type of connection	Is T55compatible?		Is an adapter provided?		Picture
	(Thread/ Clamp)	Yes/No	Connection	Yes/No	Adapter name	
Drayton Drayton	Thread: M28 x 1.0 mm	\bigotimes	No adapter available	\bigotimes	\bigotimes	
EMMETI EMMETI	Clamp: 23 mm		With adapter		Caleffi:Clip type Diameter 23mm 1/2 valve	
FAR	Thread: M23 x 1.5 mm	×	With adapter	X	×	
Fratelli - Pettinaroli	Thread: M28 x 1.5 mm	\otimes	No adapter available	X	X	
Gampper Gamppe	Clamp: Inside thread M20	\otimes	With adapter	X	×	
Gampper Gampper Armaturen	Clamp: Inside thread M22	X	With adapter	\otimes	×	
Gampper Campper Armaturen	Thread: M30 x 1.5 mm		No adapter needed	\otimes	\otimes	
Giacomini	Clamp: 22,6 mm		With adapter		Giacomini:Clip type Diameter 22.6mm 1/2 valve + short plunger	

Brand name	Type of connection	Is T55cd	ompatible?	Is an adapter provided?		Picture
	(Thread/ Clamp)	Yes/No	Connection	Yes/No	Adapter name	
Heimeier	Thread: M30 x 1.5 mm	\bigcirc	No adapter needed	\bigotimes	\bigotimes	
Herz, Honeywell	Thread: M28 x 1.5 mm	\otimes	With adapter	\bigotimes	X	
Honeywell	Thread: M30 x 1.5 mm		No adapter needed	X	X	
ista	Thread: M32 x 1.0 mm	X	With adapter	×	X	
Junkers	Thread: M30 x 1.5 mm	\bigcirc	No adapter needed	\bigotimes	X	
Landis & Gyr	Clamp: 24 mm	\otimes	No adapter available	\bigotimes	X	
MMA Markaryd		X	With adapter	\bigotimes	X	
MNG	Thread: M30 x 1.5 mm		No adapter needed	X	X	

Brand name	Type of connection	Is T55compatible?			in adapter ovided?	Picture
	(Thread/ Clamp)	Yes/No	Connection	Yes/No	Adapter name	
Myson MYSON	Thread: M28 x 1.5 mm	\bigotimes	With adapter	\bigotimes	\bigotimes	
Myson MYSON	Thread: M30 x 1.5 mm		No adapter needed	X	X	
Orkli	Thread: M28 x 1.0 mm	X	With adapter	X	X	Trans
Oventrop	Clamp: 30.5 mm	X	With adapter	X	X	
Oventrop	Clamp: 25.5 mm with 4 notches	X	With adapter	\otimes	X	
Oventrop	Clamp: 34 mm with 4 notches		With adapter	X	Danfoss:Clip type Diameter 34mm-4 notches 3/4 valve + long plunger (RAV)	
Oventrop / Buderus	Clamp: 23mm with notches	×	With adapter	\bigotimes	\bigotimes	
Oventrop / Herz	Thread: M28 x 1.5 mm	X	With adapter	\bigotimes	\bigotimes	

Brand name	Type of connection	ls T55cc	ompatible?	Is an adapter provided?		Picture
	(Thread/ Clamp)	Yes/No	Connection	Yes/No	Adapter name	
Oventrop	Thread: M30 x 1.5 mm		No adapter needed	\bigotimes	\bigotimes	
Oventrop	Thread: M30 x 1.0 mm	\otimes	With adapter	\bigotimes	X	
Oventrop / Ista	Thread: M32 x 1.0 mm	X	With adapter	\bigotimes	X	
Oventrop	Thread: M40 x 1.5 mm	\otimes	No adapter available	\bigotimes	X	
Pegler Yorkshire PEGLER PY	Thread: M30 x 1.5 mm (wide touch surface)	X	No adapter available	\bigotimes	X	
Pegler Yorkshire PEGLER PY	Thread: M28 x 1.5 mm	X	With adapter	\bigotimes	X	
Pintossi+c	Thread: M26 x 1.5 mm	X	With adapter	\bigotimes	X	
R.B.M.	Thread: M30 x 1.5 mm		No adapter needed	\bigotimes	X	

Brand name	Type of connection	ls T55compatible?		ls a pr	n adapter ovided?	Picture
Brand hame	(Thread /Clamp)	Yes/No	Connection	Yes/No	Adapter name	, iotale
ROCA BAXI GROUP	Clamp: 22.6 mm	\bigcirc	With adapter		Giacomini:Clip type Diameter 22.6mm 1/2 valve + short plunger	
SALUS	Throad		No adopter			
SSV F R S.	Thread: M30 x 1.5 mm		No adapter needed	(\times)	\times	
SALUS, SAM (Slovarm)						
SALUS.	Thread: M28 x 1.5 mm	X	With adapter	\times	\times	9)
Schlösser						
SH	Thread: M30 x 1.5 mm		No adapter needed	(\times)	\times	
Siemens						
SIEMENS	Thread: M30 x 1.5 mm		No adapter needed	\times	\times	
Siemens						
SIEMENS	Thread: M28 x 1.5 mm	X	With adapter	(\times)	\times	
Siemens						
SIEMENS	Thread: M28 x 1.0 mm	\times	With adapter	\times	\times	
Simplex						
Simplex	Thread: M30 x 1.5 mm		No adapter needed	\times	(\times)	

Brand name	Type of connection	ls T55cc	Is T55compatible?		n adapter ovided?	Picture
	(Thread/ Clamp)	Yes/No	Connection	Yes/No	Adapter name	
sunvic	Thread: M28 x 1.5 mm	\bigotimes	With adapter	\bigotimes	\bigotimes	GR
TA HYDRONICS	Thread: M28 x 1.5 mm	X	With adapter	\otimes	\bigotimes	
Vaillant, TA Heimeier Vaillant	Clamp: 30.5 mm	\bigotimes	With adapter	\bigotimes	X	
Valf Sanayli	Thread: M30 x 1.5 mm		No adapter needed	X	X	
Watts Industries	Thread: M30 x 1.5 mm		No adapter needed	X	X	

Please note: While T55 works with a great range of thermostatic radiator valves, there may be a few that T55 currently does not support. In some cases, the compatibility depends on your complete heating setup. So please bear in mind that all information in this guide is indicative and, in no way, exhaustive.